



Smartbright T8 Batten

BN012C LED20/NW L1200 G3

Polycarbonate -

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. New T8 LED batten range is perfect replacement for traditional battens with fluorescent lamps. The process of selecting, installing, and maintaining is so easy – it's a simple switch. The range offer customer to choose from various options, standalone batten, Batten with individual switch and connectable Battens in addition to 3 CCTs and 2 Wattages.

Product data

General information		
Light source color	840 neutral white	
Optical cover/lens type	Polycarbonate	
Control interface	-	
Protection class IEC	Safety class II	
Flammability mark	For mounting on normally flammable	
	surfaces	
CE mark	CE mark	
Number of products on MCB of 16 A type B 10		
Light source engine type	LED	
Operating and electrical		
Input Voltage	220 to 240 V	
Input Frequency	50 or 60 Hz	
Inrush current	14.3 A	
Power Factor (Min)	0.9	

Controls and dimming	
Dimmable	No
Mechanical and housing	
Housing Material	Polycarbonate
Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Opal
Overall length	1174 mm
Overall width	28.4 mm
Overall height	35.7 mm
Effective projected area	0.033 m²
Color	White
Approval and application	_
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]

Datasheet, 2022, May 5 data subject to change

Smartbright T8 Batten


Initial performance (IEC complian	nt)
Initial luminous flux (system flux)	2000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	0.3818, 0.3797, SDCM≤6
Initial input power	20 W
Power consumption tolerance	+/-10%

Product data	
Full product code	871951451779099
Order product name	BN012C LED20/NW L1200 G3
EAN/UPC - Product	8719514517790
Order code	911401807982
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	40
Material Nr. (12NC)	911401807982
Copy Net Weight (Piece)	0.246 kg

Application conditions		
Ambient temperature range	-20 to +40 °C	



Dimensional drawing



BN012C LED20/NW L1200 G3



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.