



GreenPerform Batten G3 BN398C

BN398C LED20/CW L600 PSU WB

Polymethyl methacrylate bowl/cover -

GreenPerform batten BN398C is a cost competitive linear solution with good performance and multiple lumen output for retail and industry applications. It offers surface mount and suspension installations to cater for different mounting options. Its multiple optic designs accommodate different applications as well.

Product data

General information		
Light source color	865 cool daylight	
Optical cover/lens type	Polymethyl methacrylate bowl/cover	
Control interface	-	
Protection class IEC	Safety class I	
Flammability mark	For mounting on normally flammable	
	surfaces	
CE mark	CE mark	
Number of products on MCB of 16 A type B 33		
Light source engine type	LED	
Operating and electrical		
Input Voltage	220-240 V	
Input Frequency	50 or 60 Hz	
Inrush current	14 A	
Power Factor (Min)	0.9	

Controls and dimming		
Dimmable	No	
Mechanical and housing		
Housing Material	Metal-Plastic	
Optical cover/lens material	Polymethyl methacrylate	
Optical cover/lens finish	Clear	
Overall length	573 mm	
Overall width	58 mm	
Overall height	58 mm	
Color	White RAL 9003	
Approval and application		
Ingress protection code	IP20 [Finger-protected]	
Mech. impact protection code	IK03 [0.35 J reinforced]	
Initial performance (IEC compliant)		
Initial luminous flux (system flux)	2000 lm	


GreenPerform Batten G3 BN398C

Luminous flux tolerance	+/-10%	
Initial LED luminaire efficacy	129 lm/W	
Init. Corr. Color Temperature	6500 K	
Init. Color Rendering Index	>80	
Initial chromaticity	SDCM<5	
Initial input power	15.5 W	
Power consumption tolerance	+/-10%	
Application conditions		
Ambient temperature range	-20 to +40 °C	
Product data		
Full product code	692382863320200	

Order product name	BN398C LED20/CW L600 PSU WB
EAN/UPC - Product	6923828633202
Order code	911401585751
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401585751
Copy Net Weight (Piece)	0.999 kg



Dimensional drawing



BN398C LED20/CW L600 PSU WB



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2022, May 9 - data subject to change