



GreenPerform Batten G3 BN398C

BN398C LED87/CW L1500 PSU DA

Polymethyl methacrylate bowl/cover -

GreenPerform batten BN398C is a cost competitive linear solution with good performance and multiple lumen output for retail and industry applications. It offers surface mount and suspension installations to cater for different mounting options. Its multiple optic designs accommodate different applications as well.

Product data

| General information | | |
|---|------------------------------------|--|
| Light source color | 865 cool daylight | |
| Optical cover/lens type | Polymethyl methacrylate bowl/cover | |
| Control interface | - | |
| Protection class IEC | Safety class I | |
| Flammability mark | For mounting on normally flammable | |
| | surfaces | |
| CE mark | CE mark | |
| Number of products on MCB of 16 A type B 24 | | |
| Light source engine type | LED | |
| | | |
| Operating and electrical | | |
| Input Voltage | 220-240 V | |
| Input Frequency | 50 or 60 Hz | |
| Inrush current | 19 A | |
| Power Factor (Min) | 0.9 | |

| Controls and dimming | |
|-------------------------------------|---------------------------|
| Dimmable | No |
| | |
| Mechanical and housing | |
| Housing Material | Metal-Plastic |
| Optical cover/lens material | Polymethyl methacrylate |
| Optical cover/lens finish | Clear |
| Overall length | 1416 mm |
| Overall width | 58 mm |
| Overall height | 58 mm |
| Color | White RAL 9003 |
| | |
| Approval and application | |
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK03 [0.35 J reinforced] |
| | |
| Initial performance (IEC compliant) | |
| Initial luminous flux (system flux) | 8500 lm |


GreenPerform Batten G3 BN398C

| Luminous flux tolerance | +/-10% | |
|--------------------------------|-----------------|--|
| Initial LED luminaire efficacy | 125 lm/W | |
| Init. Corr. Color Temperature | 6500 K | |
| Init. Color Rendering Index | >80 | |
| Initial chromaticity | SDCM<5 | |
| Initial input power | 68 W | |
| Power consumption tolerance | +/-10% | |
| | | |
| Application conditions | | |
| Ambient temperature range | -20 to +40 °C | |
| | | |
| Product data | | |
| Full product code | 692382863322600 | |

| Order product name | BN398C LED87/CW L1500 PSU DA |
|---------------------------------|------------------------------|
| EAN/UPC - Product | 6923828633226 |
| Order code | 911401585551 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 1 |
| Material Nr. (12NC) | 911401585551 |
| Copy Net Weight (Piece) | 1.999 kg |



Dimensional drawing



BN398C LED87/CW L1500 PSU DA



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2022, May 13 - data subject to change