



GreenPerform Highbay HT

BY687P LED250/CW PSR NB G2 XT EN

865 cool daylight - Power supply unit regulating - Narrow beam
 - Tempered glass

GreenPerform Highbay High Ta is an ideal solution for high temperature application and special heavy industry, enables a safe working environment with leading specification and comfortable light. In the meanwhile, lower the overall maintenance cost eventually.

Product data

General Information	
Beam angle of light source	- °
Light source color	865 cool daylight
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit regulating
Driver included	Yes
Optic type	Narrow beam
Optical cover/lens type	Tempered glass
Luminaire light beam spread	60°
Control interface	-
Connection	Flying leads/wires
Cable	Cable 0.3 m without plug
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 5 s
Flammability mark	For mounting on normally flammable surfaces

CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B 6	
EU RoHS compliant	No
Light source engine type	LED

Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Inrush current	38.3 A
Inrush time	625 ms
Power Factor (Min)	0.95

GreenPerform Highbay HT

Controls and Dimming

Dimmable	Yes
----------	-----

Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Tempered glass
Fixation material	-
Optical cover/lens finish	Clear
Overall height	165 mm
Overall diameter	520 mm
Color	Silver

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	25000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	135 lm/W
Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>80

Initial chromaticity	(0.313.0.324)SDCM<5
Initial input power	185 W
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)


Median useful life L70B50	75000 h
Median useful life L80B50	60000 h
Median useful life L90B50	45000 h

Application Conditions


Ambient temperature range	-30 to +60 °C
Maximum dim level	10% (depends on dimmer, ELV)
Suitable for random switching	No

Product Data

Full product code	911401515451
Order product name	BY687P LED250/CW PSR NB G2 XT EN
Order code	911401515451
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401515451
Net Weight (Piece)	8.999 kg



Dimensional drawing



GreenPerform High-bay gen2 BY687P-BY689P

GreenPerform Highbay HT

