
PHILIPS Lighting



Greenspace Flex

RS378B P11 940 PSU-E MB M55

940 neutral white - Electronic transformer - Gray

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

Product data

General information	
Light source color	940 neutral white
Number of gear units	1 unit
Driver/power unit/transformer	Electronic transformer
Driver included	Yes
Optical cover/lens type	Lens
Luminaire light beam spread	30°
Control interface	-
Connection	External connector
Cable	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 600 °C, duration 30 s
CE mark	CE mark
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	40
EU RoHS compliant	Yes
Light source engine type	LED
Operating and electrical	
Input Voltage	220 to 240 V

Input Frequency	50 to 60 Hz
Average CLO power consumption	845 W
Power Factor (Min)	0.9
Controls and dimming	
Dimmable	No
Mechanical and housing	
Housing Material	Aluminum
Optic material	Polymethyl methacrylate
ptical cover/lens material	Acrylate
ixation material	Aluminum
Optical cover/lens finish	Textured
Overall length	0 mm
Overall width	0 mm
Overall height	49 mm
Overall diameter	55 mm
Color	Gray
Approval and application	
ngress protection code	IP20 [Finger-protected]

Greenspace Flex

Mech. impact protection code	IK04 [0.5 J standard plus]
nitial performance (IEC compliant)	
nitial luminous flux (system flux)	1160 lm
uminous flux tolerance	+/-10%
nitial LED luminaire efficacy	106 lm/W
nit. Corr. Color Temperature	4000 K
it. Color Rendering Index	>90
nitial chromaticity	SDCM<3
nitial input power	11 W
Power consumption tolerance	+/-10%

50000 h


Maximum dim level	Not applicable
Suitable for random switching	No
Product data	
Full product code	911401721032
Order product name	RS378B P11 940 PSU-E MB M55
Order code	911401721032
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	48
Material Nr. (12NC)	911401721032
Copy Net Weight (Piece)	0.190 kg



Over time performance (IEC compliant) Median useful life L80B50

Application conditions	
Ambient temperature range	-20 to +45 °C

Dimensional drawing



RS378B P24 M70 RS378B P33 M87 107 RS378B P42 M102 116

RS378B P11 940 PSU-E MB M55



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2022, May 17 - data subject to change