



# SlimBalance

## SP550P LED25S 840 L120 PSU CD

- - Wide beam - Opal - 120°

SlimBalance is a full range of product family with sleek and elegant design helps to create attractive and differentiated space for customers. The family covers different length (600mm, 1200mm,1500mm), different end cap (round, square) and different light distribution (direct, indirect).;Its office compliant version delivers comfortable light with good quality.

### Warnings and Safety

- The product is IPX0 & as such is not protected against water ingress & as such we strongly recommend that the environment in which the luminaire is to be installed is suitably checked
- If the above advice is not taken and the luminaires are subject to water ingress, Philips / Signify cannot guarantee safe failure & product warranty will become void

### Product data

General information		Glow-wire test	
Beam angle of light source	- °	Flammability mark	-
Light source color	840 neutral white	CE mark	CE mark
Light source replaceable	No	ENEC mark	-
Number of gear units	1 unit	Warranty period	3 years
Driver/power unit/transformer	-	Constant light output	No
Driver included	Yes	Number of products on MCB of 16 A type B	24
Optic type	Wide beam	EU RoHS compliant	Yes
Optical cover/lens type	Opal	Light source engine type	LED
Luminaire light beam spread	120°	<b>Operating and electrical</b>	
Control interface	-	Input Voltage	220/240 V
Connection	Internal connector	Input Frequency	50 to 60 Hz
Cable	-	Inrush current	19 A
Protection class IEC	Safety class I		

# SlimBalance

Inrush time	280 ms
Power Factor (Min)	0.95

## Controls and dimming

Dimmable	No
----------	----

## Mechanical and housing

Housing Material	Metal
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Optical cover/lens finish	Opal
Overall length	1200 mm
Overall width	70 mm
Overall height	105 mm
Color	Silver

## Approval and application

Ingress protection code	IP20 [ Finger-protected]
Mech. impact protection code	IK03 [ 0.3 J]

## Initial performance (IEC compliant)

Initial luminous flux (system flux)	2500 lm
Luminous flux tolerance	+/-10%

Initial LED luminaire efficacy	100 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.38, 0.38) SDCM< 3
Initial input power	25 W
Power consumption tolerance	+/-10%

## Over time performance (IEC compliant)

Median useful life L70B50	50000 h
---------------------------	---------

## Application conditions


Ambient temperature range	-20 to +40 °C
Maximum dim level	Not applicable

## Product data

Full product code	911401519641
Order product name	SP550P LED25S 840 L120 PSU CD
Order code	911401519641
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	911401519641
Net Weight (Piece)	3.699 kg



## Dimensional drawing



SP550P LED25S 840 L120 PSU CD

