



# UniStrip G4

## BCP382 9LED 30K 24V A2 L30 DMX

UniStrip G4 - 610 lm - 9 W - 3000 K

UniStrip G4 is a surface-mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colours, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

### Warnings and Safety

- For outdoor use only

### Product data

| General information         |  |
|-----------------------------|--|
| Lamp colour code            | Warm white                                       |
| Light source replaceable    | No   |
| Driver included             | No   |
| Optical cover/lens type     | CLFT [ Clear flat]                               |
| Luminaire light beam spread | 16° x 35°  |
| Control interface           | Dynamix DMX                                      |
| Connection                  | 2 push-in connectors 5-pole                      |
| Cable                       | 2 cables 0.15 m with connectors 5-pole           |
| Protection class IEC        | Safety class III (III)                           |
| Flammability mark           | F [ For mounting on normally flammable surfaces] |
| CE mark                     | CE mark  |
| Light source engine type    | LED  |

|                      |  |
|----------------------|--|
| Serviceability class | Class B, the luminaire is equipped with some serviceable parts (when applicable): driver, control units, surge-protection device, front cover and mechanical parts |
|----------------------|--|

| Operating and electrical |         |
|--------------------------|---------|
| Input Voltage            | 24 DC V |
| Input frequency          | - Hz    |
| Power factor (min.)      | 0.9     |

| Controls and dimming |     |
|----------------------|-----|
| Dimmable             | Yes |

# UniStrip G4

## Mechanical and housing

|                                     |                                    |
|-------------------------------------|------------------------------------|
| Housing material                    | Aluminum extruded                  |
| Optic material                      | Polymethyl methacrylate            |
| Optical cover/lens material         | Tempered glass                     |
| Fixation material                   | Aluminium                          |
| Mounting device                     | MBA [ Mounting bracket adjustable] |
| Optical cover/lens finish           | Clear                              |
| Overall length                      | 300 mm                             |
| Overall width                       | 38 mm                              |
| Overall height                      | 47 mm                              |
| Colour                              | Dark Grey                          |
| Dimensions (height x width x depth) | 47 x 38 x 300 mm                   |

## Approval and application

|                              |   |
|------------------------------|---|
| Ingress protection code      | IP66 [ Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [ 1 J]                                   |

## Initial performance (IEC compliant)

|                                     |         |
|-------------------------------------|---------|
| Initial luminous flux (system flux) | 610 lm  |
| Luminous flux tolerance             | +/-10%  |
| Initial LED luminaire efficacy      | 68 lm/W |

|                             |        |
|-----------------------------|--------|
| Lamp colour temperature     | 3000 K |
| Colour Rendering Index      | 80     |
| Initial chromaticity        | 4 SDCM |
| Initial input power         | 9 W    |
| Power consumption tolerance | +/-10% |

## Application conditions


|                           |               |
|---------------------------|---------------|
| Ambient temperature range | -40 to +50 °C |
|---------------------------|---------------|

## Product data

|                                   |                                |
|-----------------------------------|--------------------------------|
| Full product code                 | 871951494498599                |
| Order product name                | BCP382 9LED 30K 24V A2 L30 DMX |
| EAN/UPC – product                 | 8719514944985                  |
| Order code                        | 911401739632                   |
| SAP numerator – quantity per pack | 1                              |
| Numerator – packs per outer box   | 30                             |
| SAP material                      | 911401739632                   |
| Net Weight (Piece)                | 0.599 kg                       |



## Dimensional drawing



BCP382 9LED 30K 24V A2 L30 DMX

