



UniStrip G4

BCP383 24LED 40K 220V A2 L100 DMX D2

UniStrip G4 - 2803 lm - 50 W - -

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

| General information | |
|-------------------------|--|
| Light source color | Neutral white |
| Driver included | Yes |
| Optical cover/lens type | Tempered glass |
| Control interface | Dynamix DMX |
| Connection | Flying leads/wires and 2 Push-in connector 4-pole |
| Cable | Cable 0.3 m without plug 3-pole + 2 Cables 0.3 m with connector 4-pole |
| Protection class IEC | Safety class I |
| Flammability mark | For mounting on normally flammable surfaces |
| CE mark | CE mark |

| Operating and electrical | |
|--------------------------|--------------|
| Input Voltage | 220 to 240 V |
| Input Frequency | 50 to 60 Hz |
| Inrush current | 60 A |
| Power Factor (Min) | 0.9 |

| Controls and dimming | |
|----------------------|-----|
| Dimmable | Yes |

| Mechanical and housing | |
|-----------------------------|-------------------------|
| Housing Material | Aluminum extruded |
| Optical cover/lens material | Polymethyl methacrylate |
| Effective projected area | 0.073 m ² |
| Color | Dark gray |


UniStrip G4

| | |
|--|---|
| Dimensions (Height x Width x Depth) | NaN x NaN x NaN mm |
| Approval and application | |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |
| Initial performance (IEC compliant) | |
| Initial luminous flux (system flux) | 2803 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 56 lm/W |
| Init. Corr. Color Temperature | - |
| Init. Color Rendering Index | 80 |
| Initial chromaticity | SDCM = 4 |
| Initial input power | 50 W |
| Power consumption tolerance | +/-10% |

| | |
|--|--------------------------------------|
| Application conditions | |
| Ambient temperature range | -40 to +50 °C |
| Product data | |
| Full product code | 871951492181899 |
| Order product name | BCP383 24LED 40K 220V A2 L100 DMX D2 |
| EAN/UPC - Product | 8719514921818 |
| Order code | 911401736223 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 6 |
| Material Nr. (12NC) | 911401736223 |
| Net Weight (Piece) | 3.199 kg |



Dimensional drawing



BCP383 24LED 40K 220V A2 L100 DMX D2

