



UniStrip G4

BCP384 9LED 27K 220V A2 L30 D2

UniStrip G4 - 1020 lm - 20 W - 2700 K

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

| General information | |
|-------------------------|---|
| Light source color | Warm white |
| Driver included | Yes |
| Optical cover/lens type | Tempered glass |
| Control interface | - |
| Connection | Flying leads/wires |
| Cable | Cable 0.3 m without plug 3-pole |
| Protection class IEC | Safety class I |
| Flammability mark | For mounting on normally flammable surfaces |
| CE mark | CE mark |

| Operating and electrical | |
|--------------------------|--------------|
| Input Voltage | 220 to 240 V |
| Input Frequency | 50 to 60 Hz |

| | |
|--------------------|------|
| Inrush current | 40 A |
| Power Factor (Min) | 0.9 |

| Controls and dimming | |
|----------------------|----|
| Dimmable | No |

| Mechanical and housing | |
|-------------------------------------|-------------------------|
| Housing Material | Aluminum extruded |
| Optical cover/lens material | Polymethyl methacrylate |
| Effective projected area | 0.085 m ² |
| Color | Dark gray |
| Dimensions (Height x Width x Depth) | NaN x NaN x NaN mm |

UniStrip G4

Approval and application

| | |
|------------------------------|---|
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |

Initial performance (IEC compliant)

| | |
|-------------------------------------|----------|
| Initial luminous flux (system flux) | 1020 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 51 lm/W |
| Init. Corr. Color Temperature | 2700 K |
| Init. Color Rendering Index | 80 |
| Initial chromaticity | SDCM = 4 |
| Initial input power | 20 W |
| Power consumption tolerance | +/-10% |

Application conditions


| | |
|---------------------------|---------------|
| Ambient temperature range | -40 to +50 °C |
|---------------------------|---------------|

Product data

| | |
|---------------------------------|--------------------------------|
| Full product code | 871951492186399 |
| Order product name | BCP384 9LED 27K 220V A2 L30 D2 |
| EAN/UPC - Product | 8719514921863 |
| Order code | 911401736273 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 8 |
| Material Nr. (12NC) | 911401736273 |
| Net Weight (Piece) | 1.699 kg |



Dimensional drawing



BCP384 9LED 27K 220V A2 L30 D2

