



# UniStrip G4

## BCP385 30LED 27K 220V 7 L52 D3

UniStrip G4 - 3634 lm - 60 W - 2700 K

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

### Warnings and Safety

- For outdoor use only

### Product data

General information		Inrush current	60 A
Light source color	Warm white	Power Factor (Min)	0.9
Driver included	Yes	<b>Controls and dimming</b>	
Optical cover/lens type	Tempered glass	Dimmable	No
Control interface	-	<b>Mechanical and housing</b>	
Connection	Flying leads/wires	Housing Material	Aluminum extruded
Cable	Cable 0.3 m without plug 3-pole	Optical cover/lens material	Polymethyl methacrylate
Protection class IEC	Safety class I	Effective projected area	0.135 m <sup>2</sup>
Flammability mark	For mounting on normally flammable surfaces	Color	Dark gray
CE mark	CE mark	Dimensions (Height x Width x Depth)	NaN x NaN x NaN mm
<b>Operating and electrical</b>			
Input Voltage	220 to 240 V		
Input Frequency	50 to 60 Hz		

# UniStrip G4

## Approval and application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]

## Initial performance (IEC compliant)

Initial luminous flux (system flux)	3634 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	61 lm/W
Init. Corr. Color Temperature	2700 K
Init. Color Rendering Index	80
Initial chromaticity	SDCM = 4
Initial input power	60 W
Power consumption tolerance	+/-10%

## Application conditions

Ambient temperature range	-40 to +50 °C
---------------------------	---------------

## Product data

Full product code	871951492332499
Order product name	BCP385 30LED 27K 220V 7 L52 D3
EAN/UPC - Product	8719514923324
Order code	911401736893
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	911401736893
Net Weight (Piece)	2.099 kg



## Dimensional drawing



BCP385 30LED 27K 220V 7 L52 D3

