



UniStrip G4

BCP385 30LED 40K 220V 7 L52 DMX D3

UniStrip G4 - 4345 lm - 60 W - 4000 K

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

General information	
Light source color	Neutral white
Driver included	Yes
Optical cover/lens type	Tempered glass
Control interface	Dynamix DMX
Connection	Flying leads/wires and 2 Push-in connector 4-pole
Cable	Cable 0.3 m without plug 3-pole + 2 Cables 0.3 m with connector 4-pole
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark

Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Inrush current	60 A
Power Factor (Min)	0.9

Controls and dimming	
Dimmable	Yes

Mechanical and housing	
Housing Material	Aluminum extruded
Optical cover/lens material	Polymethyl methacrylate
Effective projected area	0.135 m ²
Color	Dark gray

UniStrip G4

Dimensions (Height x Width x Depth) NaN x NaN x NaN mm

Approval and application

Ingress protection code IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code IK06 [1 J]

Initial performance (IEC compliant)

Initial luminous flux (system flux) 4345 lm
Luminous flux tolerance +/-10%
Initial LED luminaire efficacy 72 lm/W
Init. Corr. Color Temperature 4000 K
Init. Color Rendering Index 80
Initial chromaticity SDCM = 4
Initial input power 60 W
Power consumption tolerance +/-10%

Application conditions

Ambient temperature range -40 to +50 °C

Product data

Full product code 871951492231099
Order product name BCP385 30LED 40K 220V 7 L52 DMX D3
EAN/UPC - Product 8719514922310
Order code 911401736983
Numerator - Quantity Per Pack 1
Numerator - Packs per outer box 2
Material Nr. (12NC) 911401736983
Net Weight (Piece) 2.099 kg



Dimensional drawing



BCP385 30LED 40K 220V 7 L52 DMX D3

