



UniStrip G4

BCP385 30LED RGB 220V A1 L52 DMX D3

UniStrip G4 - 2545 lm - 60 W - -

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

| General information | | Operating and electrical | |
|-------------------------|--|-----------------------------|-------------------------|
| Light source color | Red, green and blue | Input Voltage | 220 to 240 V |
| Driver included | Yes | Input Frequency | 50 to 60 Hz |
| Optical cover/lens type | Tempered glass | Inrush current | 60 A |
| Control interface | Dynamic DMX | Power Factor (Min) | 0.9 |
| Connection | Flying leads/wires and 2 Push-in connector 4-pole | Controls and dimming | |
| Cable | Cable 0.3 m without plug 3-pole + 2 Cables 0.3 m with connector 4-pole | Dimmable | Yes |
| Protection class IEC | Safety class I | Mechanical and housing | |
| Flammability mark | For mounting on normally flammable surfaces | Housing Material | Aluminum extruded |
| CE mark | CE mark | Optical cover/lens material | Polymethyl methacrylate |
| | | Effective projected area | 0.135 m ² |
| | | Color | Dark gray |

UniStrip G4

| | |
|---|---|
| Dimensions (Height x Width x Depth) NaN x NaN x NaN mm | |
| Approval and application | |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |
| Initial performance (IEC compliant) | |
| Initial luminous flux (system flux) | 2545 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 42 lm/W |
| Init. Corr. Color Temperature | - |
| Init. Color Rendering Index | - |
| Initial input power | 60 W |
| Power consumption tolerance | +/-10% |

| | |
|---------------------------------|-------------------------------------|
| Application conditions | |
| Ambient temperature range | -40 to +50 °C |
| Product data | |
| Full product code | 871951492219899 |
| Order product name | BCP385 30LED RGB 220V A1 L52 DMX D3 |
| EAN/UPC - Product | 8719514922198 |
| Order code | 911401736763 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 2 |
| Material Nr. (12NC) | 911401736763 |
| Net Weight (Piece) | 2.099 kg |



Dimensional drawing



BCP385 30LED RGB 220V A1 L52 DMX D3

