



# UniStrip G4

## BCP385 60LED 30K 220V A1 L100 DMX D3

UniStrip G4 - 7072 lm - 120 W - 3000 K

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

### Warnings and Safety

- For outdoor use only

### Product data

General information	
Light source color	Warm white
Driver included	Yes
Optical cover/lens type	Tempered glass
Control interface	Dynamix DMX
Connection	Flying leads/wires and 2 Push-in connector 4-pole
Cable	Cable 0.3 m without plug 3-pole + 2 Cables 0.3 m with connector 4-pole
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark

Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Inrush current	70 A
Power Factor (Min)	0.9

Controls and dimming	
Dimmable	Yes

Mechanical and housing	
Housing Material	Aluminum extruded
Optical cover/lens material	Polymethyl methacrylate
Effective projected area	0.135 m <sup>2</sup>
Color	Dark gray

# UniStrip G4

Dimensions (Height x Width x Depth) NaN x NaN x NaN mm

## Approval and application

Ingress protection code IP66 [ Dust penetration-protected, jet-proof]

Mech. impact protection code IK06 [ 1 J]

## Initial performance (IEC compliant)

Initial luminous flux (system flux) 7072 lm

Luminous flux tolerance +/-10%

Initial LED luminaire efficacy 59 lm/W

Init. Corr. Color Temperature 3000 K

Init. Color Rendering Index 80

Initial chromaticity SDCM = 4

Initial input power 120 W

Power consumption tolerance +/-10%

## Application conditions

Ambient temperature range -40 to +50 °C

## Product data

Full product code 871951492243399

Order product name BCP385 60LED 30K 220V A1 L100 DMX D3

EAN/UPC - Product 8719514922433

Order code 911401737203

Numerator - Quantity Per Pack 1


Numerator - Packs per outer box 2

Material Nr. (12NC) 911401737203

Net Weight (Piece) 3.949 kg



## Dimensional drawing



BCP385 60LED 30K 220V A1 L100 DMX D3

