
PHILIPS Lighting



UniEdge

BCP390 4LED 40K 24V 3x90 DMX D3

UniEdge - 142 lm - 10 W - -

UniEdge is a surface mounted, exterior-rated and compact sized architectural LED edge lighting luminaire that is designed for façade and outdoor decorative lighting applications. The robust mechanical and unique optical designs make UniEdge ideal for edges lighting on windows and doors inner frames, building façades, landmarks and monuments. Available in white, monochromatic colors, RGB, RGBW and tunable white. Unique spread lens with DMX control option available to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

For outdoor use only

Product data

General information	
Light source color	Neutral white
Driver included	No
Optical cover/lens type	Tempered glass
Control interface	Dynamix DMX
Connection	2 Push-in connector 5-pole
Cable	2 cables 0.3m with connector 5-pole
Protection class IEC	Safety class III
Flammability mark	For mounting on normally flammable surfaces
CE mark	-
Operating and electrical	
Input Voltage	24 V
Input Frequency	- Hz

Inrush current	60 A
Power Factor (Min)	-
Power Factor (Nom)	-
Controls and dimming	
Dimmable	Yes
Mechanical and housing	
Housing Material	Aluminum die cast
Optical cover/lens material	Polymethyl methacrylate
Effective projected area	0.014 m²
Color	Dark gray
Dimensions (Height x Width x Depth)	NaN x NaN x NaN mm


UniEdge

Approval and application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Initial performance (IEC complia	ant)
Initial luminous flux (system flux)	142 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	14.2 lm/W
Init. Corr. Color Temperature	-
Init. Color Rendering Index	80
Initial chromaticity	4 SDCM
Initial input power	10 W
Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-40 to +50 °C

Product data	
Full product code	871951492355399
Order product name	BCP390 4LED 40K 24V 3x90 DMX D3
EAN/UPC - Product	8719514923553
Order code	911401737333
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	911401737333
Net Weight (Piece)	0.799 kg

F IP 66 IK 06

Dimensional drawing



BCP390 4LED 40K 24V 3x90 DMX D3



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.