



## EXPLOSION PROOF EMERGENCY FLOOD LIGHT

Model: SLE-EX

### SPECIFICATION:

- Input Voltage** : 220V+/-10%, 50/60Hz
- Mode of Operation** : Combined Non-maintained
- Lamp** : 2\*1W, 3W, 6W White SMD LED with lifespan 50,000 burning hours
- Safety Feature** : Over discharge and over charge protection
- Rated Duration** : 2, 3, 4 ... hours
- Power Consumption** : 3W, 6W, 8W
- Fitting Construction** : Aluminium alloy
- Mounting** : Wall, Ceiling, pendant
- Diffuser** : Toughened glass cover
- Battery Type** : Li-Ion, Ni-Cd
- Unit Dimension(mm)** : 280 X 252 X 120    **Cable Diameter(mm)**:  $\phi 8 \rightarrow \phi 10$ ,  $\phi 10 \rightarrow \phi 14$
- Test** : Wireless TEST by remote control (Optional)
- Ex-mark** : ExdIIBT6, ExdeIICT6, DIPA20TA,T7
- Compliance** : MS 983, explosive gas or hazardous area IIA,IIB,IIC

reflector matrix 3D design  
**ENVIRONMENTALLY FRIENDLY**

**IP65/66**

### Benefits:

- High durability*
- No replace bulb*
- Easy Installation*
- Maintenance Free*
- Power saving 90%*

- \* SUPER SMALL
- \* SUPER BRIGHT
- \* SUPER THIN
- \* SUPER LIGHT



Note: Due to continuous development and improvement, our company reserve the right to change specification without notice