



The most cost-effective outdoor spot light with better efficient and performance

UniPoint

Our UniPoint is designed to produce both general and accent lighting while concealing the body of the device, allowing only the light to be exposed. This design can be used to change the surroundings by adding subtle or dramatic contrasting effects. It also includes exclusive features such as energy efficiency, chromatic quality and miniaturization. We guarantee extreme reliability and high level of resistance to adverse weather conditions and vandalism

Benefits

- In stylish and very compact design
- Price point versus PHILIPS standards
- Effortless and flexible installation
- Customizing for you

Features

- High quality LED
- Different choice of light source and beam angles
- Die-cast aluminum housing + dark grey sand coating to ensure anticorrosion
- Structural waterproof technology
- IP66
- IK06
- Quality and reliability in line with all regulations

Application

- Buildings
- Statues
- Columns
- Pillars
- Eaves

Versions



UniPoint BGP312 1ED



UniPoint BGP312 3LED



UniPoint BGP312 5LED

Accessories



ZGP312 1&3LED Mounting Clip
Photo

Ordercode 911401711742



ZGP312 5LED Mounting Clip
Dimensional Drawing

Ordercode 911401711752

Approval and application	
Mech. impact protection code	IK06
Controls and dimming	
Dimmable	No
General information	
CE mark	-
Optical cover/lens type	Glass bowl/cover
Driver included	No
Light source replaceable	No
Initial performance (IEC compliant)	
Init. Color Rendering Index	>75
Light technical	
Standard tilt angle side entry	-
Standard tilt angle posttop	-
Mechanical and housing	
Color	Dark gray

General information

Order Code	Full Product Name	Luminaire light beam		
		spread	Light source color	Optic type
911401710642	BGP312 1LED 2700K NB	10°	827 warm white	Narrow beam angle 10°
911401710652	BGP312 1LED 2700K MB	25°	827 warm white	Medium beam angle 25°
911401710662	BGP312 1LED 2700K WB	40°	827 warm white	Wide beam angle 42°
911401710672	BGP312 1LED 3000K NB	10°	830 warm white	Narrow beam angle 10°
911401710682	BGP312 1LED 3000K MB	25°	830 warm white	Medium beam angle 25°
911401710692	BGP312 1LED 3000K WB	40°	830 warm white	Wide beam angle 42°
911401710702	BGP312 1LED 4000K NB	10°	840 neutral white	Narrow beam angle 10°
911401710712	BGP312 1LED 4000K MB	25°	840 neutral white	Medium beam angle 25°
911401710722	BGP312 1LED 4000K WB	40°	840 neutral white	Wide beam angle 42°
911401710732	BGP312 3LED 2700K NB	10°	827 warm white	Narrow beam angle 10°
911401710742	BGP312 3LED 2700K MB	25°	827 warm white	Medium beam angle 25°
911401710752	BGP312 3LED 2700K WB	40°	827 warm white	Wide beam angle 42°
911401710762	BGP312 3LED 3000K NB	10°	830 warm white	Narrow beam angle 10°
911401710772	BGP312 3LED 3000K MB	25°	830 warm white	Medium beam angle 25°
911401710782	BGP312 3LED 3000K WB	40°	830 warm white	Wide beam angle 42°
911401710792	BGP312 3LED 4000K NB	10°	840 neutral white	Narrow beam angle 10°
911401710802	BGP312 3LED 4000K MB	25°	840 neutral white	Medium beam angle 25°
911401710812	BGP312 3LED 4000K WB	40°	840 neutral white	Wide beam angle 42°
911401710822	BGP312 5LED 2700K NB	10°	827 warm white	Narrow beam angle 10°
911401710832	BGP312 5LED 2700K MB	25°	827 warm white	Medium beam angle 25°
911401710842	BGP312 5LED 2700K WB	40°	827 warm white	Wide beam angle 42°
911401710852	BGP312 5LED 3000K NB	10°	830 warm white	Narrow beam angle 10°
911401710862	BGP312 5LED 3000K MB	25°	830 warm white	Medium beam angle 25°
911401710872	BGP312 5LED 3000K WB	40°	830 warm white	Wide beam angle 42°
911401710882	BGP312 5LED 4000K NB	10°	840 neutral white	Narrow beam angle 10°
911401710892	BGP312 5LED 4000K MB	25°	840 neutral white	Medium beam angle 25°
911401710902	BGP312 5LED 4000K WB	40°	840 neutral white	Wide beam angle 42°

Initial performance (IEC compliant)

Order Code	Full Product Name	Init. Corr. Color	
		Temperature	Initial luminous flux
911401710642	BGP312 1LED 2700K NB	2700 K	120 lm
911401710652	BGP312 1LED 2700K MB	2700 K	120 lm
911401710662	BGP312 1LED 2700K WB	2700 K	120 lm
911401710672	BGP312 1LED 3000K NB	3000 K	120 lm
911401710682	BGP312 1LED 3000K MB	3000 K	120 lm
911401710692	BGP312 1LED 3000K WB	3000 K	120 lm
911401710702	BGP312 1LED 4000K NB	4000 K	120 lm
911401710712	BGP312 1LED 4000K MB	4000 K	120 lm
911401710722	BGP312 1LED 4000K WB	4000 K	120 lm
911401710732	BGP312 3LED 2700K NB	2700 K	330 lm
911401710742	BGP312 3LED 2700K MB	2700 K	330 lm
911401710752	BGP312 3LED 2700K WB	2700 K	330 lm
911401710762	BGP312 3LED 3000K NB	3000 K	330 lm
911401710772	BGP312 3LED 3000K MB	3000 K	330 lm

Order Code	Full Product Name	Init. Corr. Color	
		Temperature	Initial luminous flux
911401710782	BGP312 3LED 3000K WB	3000 K	330 lm
911401710792	BGP312 3LED 4000K NB	4000 K	330 lm
911401710802	BGP312 3LED 4000K MB	4000 K	330 lm
911401710812	BGP312 3LED 4000K WB	4000 K	330 lm
911401710822	BGP312 5LED 2700K NB	2700 K	595 lm
911401710832	BGP312 5LED 2700K MB	2700 K	595 lm
911401710842	BGP312 5LED 2700K WB	2700 K	595 lm
911401710852	BGP312 5LED 3000K NB	3000 K	595 lm
911401710862	BGP312 5LED 3000K MB	3000 K	595 lm
911401710872	BGP312 5LED 3000K WB	3000 K	595 lm
911401710882	BGP312 5LED 4000K NB	4000 K	595 lm
911401710892	BGP312 5LED 4000K MB	4000 K	595 lm
911401710902	BGP312 5LED 4000K WB	4000 K	595 lm

