



# Product Description

## EB-Certalume for PLT/C lamps

Affordable, reliable, high frequency electronic ballast for 4-pin PL-T and PL-C fluorescent lamps, ideal alternative for electromagnetic (EM) ballasts. The ballast is primarily designed for Indoor application. For outdoor application, the luminaire should be minimum Class II and need to be sufficiently protected against water & dust. The installation should also be guard against any lightning surge or any other necessary electrical protection as deemed in such typical installation & application.

### Benefits

- Energy efficient, saving 25% energy compared to electromagnetic “C-type” ballasts
- The EB-C TL5 range has a robust design and meets safety, EMC and Immunity tests including safety approbation via an external test-house covering IEC/EN 61347.
- Ideal alternative for electromagnetic ballast, no ignitor needed. Pre wired, Lamp/ mains wires and lamp holders are included for easy installation.
- Same size as electromagnetic ballast so ideal for replacements

### Features

- Energy efficient CELMA A3
- Complying to CCC certificate including safety acc IEC 61347
- Robust design for 20.000 hour lifetime and 3.000 on/off switches on one lamp.
- Rapid, flicker-free lamp start (< 1.6 s)
- High power factor 0.95 with THD <25%
- EMC compliant to EN 55015 2006 + A1 2007
- Wide voltage range for ignition and operation (165V-253V)
- 45 degree connector for easy connection with push button release

# EB-Certalume for PLT/C lamps

## Application


- Designed for applications where lamps burn for a long period of time and switching cycle (on/off) is infrequent. Typical areas of application include:
- Professional indoor applications (e.g. offices and hotels)
- Department stores, shops, supermarkets, convenient stores and public area's
- Indoor lighting boxes
- Homes

## Versions



EB-C 113 PL-T/C 220-240V 50/60Hz

## Dimensional drawing



Product	D1	C1	A1	A2	B1
EB-C 218 PL-T/C 220-240V 50/60Hz	4.2 mm	31.0 mm	94.0 mm	86.0 mm	72.0 mm
EB-C 126 PL-T/C 220-240V 50/60Hz	4.2 mm	31.0 mm	94.0 mm	86.0 mm	72.0 mm
EB-C 226 PL-T/C 220-240V 50/60Hz	4.2 mm	31.0 mm	94.0 mm	86.0 mm	72.0 mm
EB-C 113 PL-T/C 220-240V 50/60Hz	4.2 mm	31.0 mm	94.0 mm	86.0 mm	72.0 mm
EB-C 213 PL-T/C 220-240V 50/60Hz	4.2 mm	31.0 mm	94.0 mm	86.0 mm	72.0 mm
EB-C 118 PL-T/C 220-240V 50/60Hz	4.2 mm	31.0 mm	94.0 mm	86.0 mm	72.0 mm

### Approval and application

Energy Efficiency Index A2

### Operating and electrical

Input Frequency 50 to 60 Hz

Input Voltage 220 to 240 V

### General information

Number Of Products On MCB (16A Type B) (Nom) 20

Lamp Type PL-T/C

# EB-Certalume for PLT/C lamps

## General information

Order Code	Full Product Name	Number Of Lamps
913713198414	EB-C 113 PL-T/C 220-240V 50/60Hz	1 piece/unit
913713198514	EB-C 213 PL-T/C 220-240V 50/60Hz	2 piece/unit
913713198614	EB-C 118 PL-T/C 220-240V 50/60Hz	1 piece/unit

Order Code	Full Product Name	Number Of Lamps
913713198714	EB-C 218 PL-T/C 220-240V 50/60Hz	2 piece/unit
913713198814	EB-C 126 PL-T/C 220-240V 50/60Hz	1 piece/unit
913713198914	EB-C 226 PL-T/C 220-240V 50/60Hz	2 piece/unit

## System characteristics

Order Code	Full Product Name	Lamp Power	Rated Ballast-
		On PL-T/C	Lamp Power
913713198414	EB-C 113 PL-T/C 220-240V 50/60Hz	13.0 W	13 W
913713198514	EB-C 213 PL-T/C 220-240V 50/60Hz	13.0 W	13 W
913713198614	EB-C 118 PL-T/C 220-240V 50/60Hz	16.0 W	18 W
913713198714	EB-C 218 PL-T/C 220-240V 50/60Hz	16.5 W	18 W

Order Code	Full Product Name	Lamp Power	Rated Ballast-
		On PL-T/C	Lamp Power
913713198814	EB-C 126 PL-T/C 220-240V 50/60Hz	24.5 W	26 W
913713198914	EB-C 226 PL-T/C 220-240V 50/60Hz	24.5 W	26 W

## Mechanical and housing

Order Code	Full Product Name	Housing
913713198414	EB-C 113 PL-T/C 220-240V 50/60Hz	-
913713198514	EB-C 213 PL-T/C 220-240V 50/60Hz	-
913713198614	EB-C 118 PL-T/C 220-240V 50/60Hz	-

Order Code	Full Product Name	Housing
913713198714	EB-C 218 PL-T/C 220-240V 50/60Hz	-
913713198814	EB-C 126 PL-T/C 220-240V 50/60Hz	-
913713198914	EB-C 226 PL-T/C 220-240V 50/60Hz	-

