



EXPLOSION PROOF EMERGENCY EXIT LIGHT

Model: SLES-EX

SPECIFICATION:

- Input Voltage** : 220V+/-10%, 50/60Hz
- Mode of Operation** : Combined maintained
- Lamp** : 3W, 6W, 8W White SMD LED with lifespan 50,000 burning hours
- Safety Feature** : Over discharge and over free charge protection
- Rated Duration** : 2, 3, 4 ... hours
- Power Consumption** : 3W, 6W, 8W
- Fitting Construction** : Aluminium alloy
- Mounting** : Wall, Ceiling, pendant
- Diffuser** : Toughened glass cover
- Battery Type** : Li-Ion, Ni-Cd
- Unit Dimension(mm)** : L365 X H170 X D73
- Test** : Wireless TEST by remote control (Optional)
- Ex-mark** : ExdIIBT6, ExdeIICT6, DIPA20TA,T7
- Compliance** : MS 983, explosive gas or hazardous area IIA,IIB,IIC
- Cable Diameter(mm)** : $\Phi 8 \rightarrow \Phi 10$, $\Phi 10 \rightarrow \Phi 14$
- Weigh** : 1.8kgs



ENVIRONMENTALLY FRIENDLY

IP65/66



Note: Due to continuous development and improvement, our company reserve the right to change specification without notice