



GreenPerform Direct LED Panel

RC099V G2 LED36/865 PSU W30L120 OC

Polystyrene bowl/cover prismatic -

GreenPerform RC099V G2 direct Panel is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600x600, 300x1200, and 600x1200mm with max: 110lm/w system efficacy. Its UGR19 version brings more visual comfort to the office. By means of its compact design, the housing height (without driver) reaches only 35mm which gives more flexibility for recessed installation.

Product data

General information		Controls and dimming	
Light source color	865 cool daylight	Dimmable	No
Optical cover/lens type	Polystyrene bowl/cover prismatic	Mechanical and housing	
Control interface	-	Housing Material	Steel
Protection class IEC	Safety class II	Optical cover/lens material	Polystyrene
CE mark	CE mark	Optical cover/lens finish	Opal
Number of products on MCB of 16 A type B	24	Overall length	1195 mm
Light source engine type	LED	Overall width	295 mm
Operating and electrical		Overall height	57 mm
Input Voltage	220 to 240 V	Color	White RAL 9003
Input Frequency	50 or 60 Hz	Approval and application	
Power Factor (Min)	0.9	Ingress protection code	IP20 [Finger-protected]
		Mech. impact protection code	-

GreenPerform Direct LED Panel

Initial performance (IEC compliant)

Initial luminous flux (system flux)	3600 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>80
Initial input power	35 W
Power consumption tolerance	+/-10%

Application conditions


Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Product data

Full product code	692382864369099
Order product name	RC099V G2 LED36/865 PSU W30L120 OC
EAN/UPC - Product	6923828643690
Order code	911401700873
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	911401700873
Copy Net Weight (Piece)	2.300 kg



Dimensional drawing



RC099V G2 LED36/865 PSU W30L120 OC

