



Smartbright Waterproof G3 WT068C

WT068C CW LED18 L600 PSU TW1

Philips Smartbright Waterproof G3 batten offers exceptional value. It is Perfect for everyday lighting installations. Available in 3 standard sizes, it has option of Standard and through wiring version.


Product data

General information		Optical cover/lens material	
Light source color	865 cool daylight	Optical cover/lens finish	Opal
Optical cover/lens type	-	Overall length	640 mm
Control interface	-	Overall width	69 mm
Protection class IEC	Safety class II	Overall height	74 mm
CE mark	CE mark	Color	White and gray
Number of products on MCB of 16 A type B 1			
Light source engine type	LED		
Operating and electrical		Approval and application	
Input Voltage	220 to 240 V	Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Input Frequency	50 or 60 Hz	Mech. impact protection code	IK06 [1 J]
Power Factor (Min)	0.9		
Controls and dimming		Initial performance (IEC compliant)	
Dimmable	No	Initial luminous flux (system flux)	1800 lm
		Luminous flux tolerance	+/-10%
		Initial LED luminaire efficacy	110 lm/W
		Init. Corr. Color Temperature	6500 K
		Init. Color Rendering Index	>80
Mechanical and housing		Initial input power	16.5 W
Housing Material	Polycarbonate		

Smartbright Waterproof G3 WT068C


Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-20 to +45 °C
Product data	
Full product code	871016336065299
Order product name	WT068C CW LED18 L600 PSU TW1
EAN/UPC - Product	8710163360652

Order code	911401881980
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401881980
Net Weight (Piece)	0.290 kg



Dimensional drawing

WT068C TW-2ft



WT068C CW LED18 L600 PSU TW1

