

# Smartbright Waterproof G3 WT068C

## WT068C NW LED18 L600 PSU

Philips Smartbright Waterproof G3 batten offers exceptional value. It is Perfect for everyday lighting installations. Available in 3 standard sizes, it has option of Standard and through wiring version.


### Product data

General information		Optical cover/lens material	
Light source color	840 neutral white	Optical cover/lens material	Polycarbonate
Optical cover/lens type	-	Optical cover/lens finish	Opal
Control interface	-	Overall length	598 mm
Protection class IEC	Safety class II	Overall width	69 mm
CE mark	CE mark	Overall height	74 mm
Number of products on MCB of 16 A type B 1		Color	White and gray
Light source engine type	LED	<b>Approval and application</b>	
<b>Operating and electrical</b>		Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Input Voltage	220 to 240 V	Mech. impact protection code	IK06 [ 1 J]
Input Frequency	50 or 60 Hz	<b>Initial performance (IEC compliant)</b>	
Power Factor (Min)	0.9	Initial luminous flux (system flux)	1800 lm
<b>Controls and dimming</b>		Luminous flux tolerance	+/-10%
Dimmable	No	Initial LED luminaire efficacy	110 lm/W
<b>Mechanical and housing</b>		Init. Corr. Color Temperature	4000 K
Housing Material	Polycarbonate	Init. Color Rendering Index	>80
		Initial input power	16.5 W

# Smartbright Waterproof G3 WT068C


Power consumption tolerance	+/-10%
<b>Application conditions</b>	
Ambient temperature range	-20 to +45 °C
<b>Product data</b>	
Full product code	871016336062199
Order product name	WT068C NW LED18 L600 PSU
EAN/UPC - Product	8710163360621

Order code	911401881680
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401881680
Net Weight (Piece)	0.270 kg



## Dimensional drawing

WT068C-2ft



WT068C NW LED18 L600 PSU

