



# **GreenPerform Waterproof G3**

# WT198X LED20S/840 WIA L600

Acrylic bowl/cover frosted -

GreenPerform Waterproof G3 is a superb choice for hard-working applications. Not only does it provide excellent optical performance, it also delivers substantial energy saving. And because it works seamlessly with IoT software like Interact, it also offers the option of customization, convenience, and data-driven insights.

### **Product data**

General information	
Light source color	840 neutral white
Optical cover/lens type	Acrylic bowl/cover frosted
Control interface	InterAct Pro
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable
	surfaces
CE mark	CE mark
Number of products on MCB of 16 A type	<b>B</b> 24
Light source engine type	LED
Operating and electrical	
Input Voltage	220-240 V
Input Frequency	50 or 60 Hz
Inrush current	19 A
Power Factor (Min)	0.9

Controls and dimming	
Dimmable	Wireless Dim
Mechanical and housing	
Housing Material	Polycarbonate
Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Frosted
Overall length	665 mm
Overall width	80 mm
Effective projected area	0.053 m²
Color	Gray
Approval and application	
Ingress protection code	IP65 [ Dust penetration-protected, jet-
	proof]
Mech. impact protection code	6 J (IK08)

Datasheet, 2022, July 26 data subject to change


# **GreenPerform Waterproof G3**

Initial performance (IEC compliant)	
Initial luminous flux (system flux)	2000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	125 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.3742,0.3698) SDCM<3
Initial input power	16 W
Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-20 to +45 ℃

Product data	
Order product name	WT198X LED20S/840 WIA L600
Order code	911401549981
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	9
Material Nr. (12NC)	911401549981
Copy Net Weight (Piece)	0.790 kg



## Dimensional drawing



WT198X LED20S/840 WIA L600



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.