

# **Truefashion Projector GCGM**

## **GD700B 2XLED10 830 PSU MB WH**

#### Lens

Truefashion Projector is offering a retail segment with attractive outlook design, excellent quality of light & dedicated light recipe as well as system connectivity, to create a comfortable ambiance and impressive shopping experience to stimulate the store sales for retail customers.

#### **Warnings and Safety**

· 3 years

#### **Product data**

General information	
Light source color	830 warm white
Optical cover/lens type	Lens
Control interface	-
Protection class IEC	Safety class II
CE mark	CE mark
Number of products on MCB of 16 A type B	1
Light source engine type	LED
Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.91

Dimmable  No  Mechanical and housing  Housing Material  Optical cover/lens material  Optical cover/lens finish  Overall length  Overall width  115 mm  Overall height  75 mm  Color  White RAL 9003	Controls and dimming	
Housing Material Aluminum  Optical cover/lens material Polymethyl methacrylate  Optical cover/lens finish  Overall length 217 mm  Overall width 115 mm  Overall height 75 mm  Color White RAL 9003  Approval and application	Dimmable	No
Housing Material Aluminum  Optical cover/lens material Polymethyl methacrylate  Optical cover/lens finish  Overall length 217 mm  Overall width 115 mm  Overall height 75 mm  Color White RAL 9003  Approval and application		
Optical cover/lens material Polymethyl methacrylate  Optical cover/lens finish -  Overall length 217 mm  Overall width 115 mm  Overall height 75 mm  Color White RAL 9003	Mechanical and housing	
Optical cover/lens finish  Overall length  217 mm  Overall width  115 mm  Overall height  75 mm  Color  White RAL 9003	Housing Material	Aluminum
Overall length 217 mm Overall width 115 mm Overall height 75 mm Color White RAL 9003  Approval and application	Optical cover/lens material	Polymethyl methacrylate
Overall width 115 mm Overall height 75 mm Color White RAL 9003  Approval and application	Optical cover/lens finish	-
Overall height 75 mm  Color White RAL 9003  Approval and application	Overall length	217 mm
Color White RAL 9003  Approval and application	Overall width	115 mm
Approval and application	Overall height	75 mm
	Color	White RAL 9003
	Approval and application	
Ingress protection code IP20 [ Finger-protected]	Ingress protection code	IP20 [ Finger-protected]

Datasheet, 2022, September 4 data subject to change


# **Truefashion Projector GCGM**

Mech. impact protection code		
Initial performance (IEC compliant)		
Initial luminous flux (system flux)	1884 lm	
Luminous flux tolerance	+/-10%	
Initial LED luminaire efficacy	114 lm/W	
Init. Corr. Color Temperature	3000 K	
Init. Color Rendering Index	>80	
Initial input power	16 W	
Power consumption tolerance	+/-10%	
Application conditions		
Ambient temperature range	-15 to +35 °C	

Product data	
Full product code	911401518771
Order product name	GD700B 2XLED10 830 PSU MB WH
Order code	911401518771
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401518771
Net Weight (Piece)	0.900 kg



## Dimensional drawing



GD700B 2XLED10 830 PSU MB WH



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.