



Truefashion Projector GCGM

GD700B LED10 830 PSU MB WH

Lens

Truefashion Projector is offering a retail segment with attractive outlook design, excellent quality of light & dedicated light recipe as well as system connectivity, to create a comfortable ambiance and impressive shopping experience to stimulate the store sales for retail customers.

Warnings and Safety

- 3 years

Product data

General information		Controls and dimming	
Light source color	830 warm white	Dimmable	No
Optical cover/lens type	Lens	Mechanical and housing	
Control interface	-	Housing Material	Aluminum
Protection class IEC	Safety class II	Optical cover/lens material	Polymethyl methacrylate
CE mark	CE mark	Optical cover/lens finish	-
Number of products on MCB of 16 A type B	1	Overall length	100 mm
Light source engine type	LED	Overall width	100 mm
Operating and electrical		Overall height	75 mm
Input Voltage	220 to 240 V	Color	White RAL 9003
Input Frequency	50 or 60 Hz	Approval and application	
Power Factor (Min)	0.91	Ingress protection code	IP20 [Finger-protected]


Truefashion Projector GCGM

Mech. impact protection code	-
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	942 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	114 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>80
Initial input power	8 W
Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-15 to +35 °C

Product data	
Full product code	911401518371
Order product name	GD700B LED10 830 PSU MB WH
Order code	911401518371
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401518371
Net Weight (Piece)	0.350 kg



Dimensional drawing



GD700B LED10 830 PSU MB WH

