



# **Truefashion Projector GCGM**

# RS700B LED30 940PW PSU MB WH

Lens -

Truefashion Projector is offering a retail segment with attractive outlook design, excellent quality of light & dedicated light recipe as well as system connectivity, to create a comfortable ambiance and impressive shopping experience to stimulate the store sales for retail customers.

### **Warnings and Safety**

· 3 years

#### **Product data**

| General information                      |                   |
|--|-------------------|
| Light source color                       | 940 neutral white |
| Optical cover/lens type                  | Lens              |
| Control interface                        | -                 |
| Protection class IEC                     | Safety class II   |
| CE mark                                  | CE mark           |
| Number of products on MCB of 16 A type B | 1                 |
| Light source engine type                 | LED               |
|  |                   |
| Operating and electrical                 |                   |
| Input Voltage                            | 220 to 240 V      |
| Input Frequency                          | 50 or 60 Hz       |
| Power Factor (Min)                       | 0.95              |
|  |                   |

| Controls and dimming         |                          |
|------------------------------|--------------------------|
| Dimmable                     | No                       |
|                              |                          |
| Mechanical and housing       |                          |
| Housing Material             | Aluminum                 |
| Optical cover/lens material  | Polymethyl methacrylate  |
| Optical cover/lens finish    | -                        |
| Overall height               | 100 mm                   |
| Overall diameter             | 111 mm                   |
| Color                        | White RAL 9003           |
|                              |                          |
| Approval and application     |                          |
| Ingress protection code      | IP20 [ Finger-protected] |
| Mech. impact protection code | -                        |

Datasheet, 2022, July 26 data subject to change


# **Truefashion Projector GCGM**

| Initial performance (IEC compliant) |               |  |
|-------------------------------------|---------------|--|
| Initial luminous flux (system flux) | 3076 lm       |  |
| Luminous flux tolerance             | +/-10%        |  |
| Initial LED luminaire efficacy      | 100 lm/W      |  |
| Init. Corr. Color Temperature       | 4000 K        |  |
| Init. Color Rendering Index         | >90           |  |
| Initial input power                 | 31 W          |  |
| Power consumption tolerance         | +/-10%        |  |
| Application conditions              |               |  |
| Ambient temperature range           | -15 to +35 °C |  |

| Product data                    |                              |  |
|---------------------------------|------------------------------|--|
| Full product code               | 911401520971                 |  |
| Order product name              | RS700B LED30 940PW PSU MB WH |  |
| Order code                      | 911401520971                 |  |
| Numerator - Quantity Per Pack   | 1                            |  |
| Numerator - Packs per outer box | 1                            |  |
| Material Nr. (12NC)             | 911401520971                 |  |
| Copy Net Weight (Piece)         | 0.630 kg                     |  |



# Dimensional drawing



RS700B LED30 940PW PSU MB WH



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.