



Truefashion Projector GCGM

ST700T LED20 830 PSU WB 1C BK

Power supply unit - Beam angle 30° - Lens - 30°

Truefashion Projector is offering a retail segment with attractive outlook design, excellent quality of light & dedicated light recipe as well as system connectivity, to create a comfortable ambiance and impressive shopping experience to stimulate the store sales for retail customers.

Warnings and Safety

- 3 years

Product data

General information		Operating and electrical	
Beam angle of light source	120 °	ENEC mark	-
Light source color	830 warm white	Warranty period	3 years
Light source replaceable	No	Constant light output	No
Number of gear units	1 unit	Number of products on MCB of 16 A type B	-
Driver/power unit/transformer	Power supply unit	EU RoHS compliant	Yes
Driver included	Yes	Light source engine type	-
Optic type	Beam angle 30°	Controls and dimming	
Optical cover/lens type	Lens	Dimmable	No
Luminaire light beam spread	30°		
Control interface	-		
Connection	Track		
Cable	-		
Protection class IEC	Safety class II		
CE mark	CE mark		

Truefashion Projector GCGM

Mechanical and housing

Housing Material	Aluminum
Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover/lens material	Polymethyl methacrylate
Fixation material	Aluminum
Optical cover/lens finish	Clear
Overall length	164 mm
Overall height	185 mm
Overall diameter	66 mm
Color	Black

Approval and application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	-

Initial performance (IEC compliant)

Initial luminous flux (system flux)	1930.4 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	86.7 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.434, 0.403) SDCM<3
Initial input power	22.3 W

Power consumption tolerance	+/-10%
-----------------------------	--------

Over time performance (IEC compliant)

Driver failure rate at 5000 h	0.14 %
Median useful life L70B50	50000 h
Median useful life L80B50	50000 h
Median useful life L90B50	32600 h

Application conditions


Ambient temperature range	-20 to +35 °C
Maximum dim level	Not applicable
Suitable for random switching	No

Product data

Full product code	911401562361
Order product name	ST700T LED20 830 PSU WB 1C BK
Order code	911401562361
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401562361
Net Weight (Piece)	0.450 kg



Dimensional drawing



ST700T LED20 830 PSU WB 1C BK

