



# Truefashion Projector GCGM

## ST700T LED30 930PW PSD VLC WB BK

Fashion proof optic beam angle 36°

Truefashion Projector is offering a retail segment with attractive outlook design, excellent quality of light & dedicated light recipe as well as system connectivity, to create a comfortable ambiance and impressive shopping experience to stimulate the store sales for retail customers.

### Warnings and Safety

- 3 years

### Product data

General information		Controls and dimming	
Light source color	PremiumWhite with CRI ≥90, and color temperature 3000K	Dimmable	No
Optical cover/lens type	Fashion proof optic beam angle 36°	Mechanical and housing	
Control interface	DALI	Housing Material	Aluminum
Protection class IEC	Safety class II	Optical cover/lens material	Polymethyl methacrylate
CE mark	CE mark	Optical cover/lens finish	Clear
Number of products on MCB of 16 A type B	-	Overall length	226 mm
Light source engine type	-	Overall height	194 mm
Operating and electrical		Overall diameter	80 mm
Input Voltage	220 to 240 V	Color	White and black
Input Frequency	50 or 60 Hz	Approval and application	
Power Factor (Min)	0.9	Ingress protection code	IP20 [ Finger-protected]

# Truefashion Projector GCGM

Mech. impact protection code	-
------------------------------	---

## Initial performance (IEC compliant)

Initial luminous flux (system flux)	3001.68 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	85.84686390532543 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>90
Initial input power	35 W
Power consumption tolerance	+/-10%


## Application conditions

Ambient temperature range	-20 to +35 °C
---------------------------	---------------

<b>Product data</b>	
Full product code	911401576061
Order product name	ST700T LED30 930PW PSD VLC WB BK
Order code	911401576061
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401576061
Net Weight (Piece)	0.899 kg



## Dimensional drawing



ST700T LED30 930PW PSD VLC WB BK

