



Truefashion Projector GCGM

ST700T LED40 930PC PSU MB 1C WH HB

Power supply unit - Beam angle 24° - Lens - 24°

Truefashion Projector is offering a retail segment with attractive outlook design, excellent quality of light & dedicated light recipe as well as system connectivity, to create a comfortable ambiance and impressive shopping experience to stimulate the store sales for retail customers.

Warnings and Safety

- 3 years

Product data

General information		Operating and electrical	
Beam angle of light source	120 °	ENEC mark	-
Light source color	930 warm white	Warranty period	3 years
Light source replaceable	No	Constant light output	No
Number of gear units	1 unit	Number of products on MCB of 16 A type B	-
Driver/power unit/transformer	Power supply unit	EU RoHS compliant	Yes
Driver included	Yes	Light source engine type	-
Optic type	Beam angle 24°	Controls and dimming	
Optical cover/lens type	Lens	Dimmable	No
Luminaire light beam spread	24°	Input Voltage	220 to 240 V
Control interface	-	Input Frequency	50 or 60 Hz
Connection	Track	Power Factor (Min)	0.9
Cable	-		
Protection class IEC	Safety class II		
CE mark	CE mark		

Truefashion Projector GCGM

Mechanical and housing

Housing Material	Aluminum
Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover/lens material	Polymethyl methacrylate
Fixation material	Aluminum
Optical cover/lens finish	Clear
Overall length	223 mm
Overall height	185 mm
Overall diameter	80 mm
Color	White

Approval and application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	-

Initial performance (IEC compliant)

Initial luminous flux (system flux)	1953.45 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	44.6 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.422, 0.386) SDCM<3
Initial input power	43.8 W

Power consumption tolerance	+/-10%
-----------------------------	--------

Over time performance (IEC compliant)

Driver failure rate at 5000 h	0.23 %
Median useful life L70B50	50000 h
Median useful life L80B50	38700 h
Median useful life L90B50	18200 h

Application conditions


Ambient temperature range	-20 to +35 °C
Maximum dim level	Not applicable
Suitable for random switching	No

Product data

Full product code	911401548261
Order product name	ST700T LED40 930PC PSU MB 1C WH HB
Order code	911401548261
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401548261
Net Weight (Piece)	0.599 kg



Dimensional drawing



ST700T LED40 930PC PSU MB 1C WH HB

