



Simplicity with elegance

SlimBalance G2

SlimBalance G2 SP560P is a cost effective linear suspension office offer with multiple lumen output and product sizes. With its sleek and elegant design, it helps create attractive and differentiated office spaces for customers. This family has 3 different widths: 30mm, 60mm and 90mm. Its max diffuser length reaches 12m which provides no diffuser gap between 2 luminaires after installation and better visual comfort in office. PSU, Dali, Interact System are offered by this new generation for easy and flexible light control. By means of its quick connector, it is easier for on-site installation as well.

Benefits

- Multiple lengths and widths to fit different office applications
- Max 12m continuous diffuser installation makes office visually better
- System options available to easily control the lights

Features

- Lengths options with 600/1200mm; width options with 30/60/90mm
- CRI 80 with flicker free
- Dali and Interact system available

Application

- Office
- Meeting room
- Indoor public area

SlimBalance G2

Versions



SlimBalance G2

SlimBalance G2

SlimBalance G2

Product details



SlimBalance G2



SlimBalance G2



SlimBalance G2

Application conditions

| | |
|---------------------------|---------------|
| Ambient temperature range | -20 to +40 °C |
|---------------------------|---------------|

Approval and application

| | |
|------------------------------|------|
| Mech. impact protection code | IK02 |
|------------------------------|------|

Operating and electrical

| | |
|---------------|-----------|
| Input Voltage | 220-240 V |
|---------------|-----------|

General information

| | |
|-------------------------|---|
| CE mark | CE mark |
| Protection class IEC | Safety class I |
| Optical cover/lens type | Reflector |
| Flammability mark | For mounting on normally flammable surfaces |

Initial performance (IEC compliant)

| | |
|--------------------------------|--------------------------|
| Initial chromaticity | (0.384, 0.380) SDCM 4 |
| Init. Corr. Color Temperature | 4000 K |
| Init. Color Rendering Index | >80 |
| Initial LED luminaire efficacy | 100 lm/W |
| Luminous flux tolerance | +/-10% |

Mechanical and housing

| | |
|-------|----------------|
| Color | White RAL 9003 |
|-------|----------------|

Approval and application

| Order Code | Full Product Name | Ingress protection code |
|--------------|--------------------------------|-------------------------|
| 911401550781 | SP560P LED6/840 L60W3 SD PSU | IP40 |
| 911401551281 | SP560P LED6/840 L60W3 CD PSU | IP20 |
| 911401552781 | SP560P LED12/840 L120W3 SD PSU | IP40 |
| 911401553281 | SP560P LED12/840 L120W3 CD PSU | IP20 |
| 911401550881 | SP560P LED12/840 L60W6 SD PSU | IP40 |
| 911401550981 | SP560P LED20/840 L60W6 SD PSU | IP40 |
| 911401551381 | SP560P LED12/840 L60W6 CD PSU | IP20 |
| 911401551481 | SP560P LED20/840 L60W6 CD PSU | IP20 |
| 911401552881 | SP560P LED25/840 L120W6 SD PSU | IP40 |
| 911401552981 | SP560P LED40/840 L120W6 SD PSU | IP40 |
| 911401553381 | SP560P LED25/840 L120W6 CD PSU | IP20 |
| 911401553481 | SP560P LED40/840 L120W6 CD PSU | IP20 |
| 911401555181 | SP560P LED20/840 L60W6 SD PSD | IP40 |
| 911401555281 | SP560P LED40/840 L120W6 SD PSD | IP40 |
| 911401555781 | SP560P LED20/840 L60W6 CD PSD | IP20 |
| 911401555881 | SP560P LED40/840 L120W6 CD PSD | IP20 |
| 911401551081 | SP560P LED12/840 L60W9 SD PSU | IP40 |
| 911401551181 | SP560P LED20/840 L60W9 SD PSU | IP40 |
| 911401551581 | SP560P LED12/840 L60W9 CD PSU | IP20 |
| 911401551681 | SP560P LED20/840 L60W9 CD PSU | IP20 |
| 911401553081 | SP560P LED25/840 L120W9 SD PSU | IP40 |
| 911401553181 | SP560P LED40/840 L120W9 SD PSU | IP40 |
| 911401553581 | SP560P LED25/840 L120W9 CD PSU | IP20 |
| 911401553681 | SP560P LED40/840 L120W9 CD PSU | IP20 |
| 911401555381 | SP560P LED20/840 L60W9 SD PSD | IP40 |
| 911401555481 | SP560P LED40/840 L120W9 SD PSD | IP40 |
| 911401555981 | SP560P LED20/840 L60W9 CD PSD | IP20 |
| 911401556081 | SP560P LED40/840 L120W9 CD PSD | IP20 |

Controls and dimming

| Order Code | Full Product Name | Dimmable | Order Code | Full Product Name | Dimmable |
|--------------|--------------------------------|----------|--------------|--------------------------------|----------|
| 911401550781 | SP560P LED6/840 L60W3 SD PSU | No | 911401555781 | SP560P LED20/840 L60W6 CD PSD | Yes |
| 911401551281 | SP560P LED6/840 L60W3 CD PSU | No | 911401555881 | SP560P LED40/840 L120W6 CD PSD | Yes |
| 911401552781 | SP560P LED12/840 L120W3 SD PSU | No | 911401551081 | SP560P LED12/840 L60W9 SD PSU | No |
| 911401553281 | SP560P LED12/840 L120W3 CD PSU | No | 911401551181 | SP560P LED20/840 L60W9 SD PSU | No |
| 911401550881 | SP560P LED12/840 L60W6 SD PSU | No | 911401551581 | SP560P LED12/840 L60W9 CD PSU | No |
| 911401550981 | SP560P LED20/840 L60W6 SD PSU | No | 911401551681 | SP560P LED20/840 L60W9 CD PSU | No |
| 911401551381 | SP560P LED12/840 L60W6 CD PSU | No | 911401553081 | SP560P LED25/840 L120W9 SD PSU | No |
| 911401551481 | SP560P LED20/840 L60W6 CD PSU | No | 911401553181 | SP560P LED40/840 L120W9 SD PSU | No |
| 911401552881 | SP560P LED25/840 L120W6 SD PSU | No | 911401553581 | SP560P LED25/840 L120W9 CD PSU | No |
| 911401552981 | SP560P LED40/840 L120W6 SD PSU | No | 911401553681 | SP560P LED40/840 L120W9 CD PSU | No |
| 911401553381 | SP560P LED25/840 L120W6 CD PSU | No | 911401555381 | SP560P LED20/840 L60W9 SD PSD | Yes |
| 911401553481 | SP560P LED40/840 L120W6 CD PSU | No | 911401555481 | SP560P LED40/840 L120W9 SD PSD | Yes |
| 911401555181 | SP560P LED20/840 L60W6 SD PSD | Yes | 911401555981 | SP560P LED20/840 L60W9 CD PSD | Yes |
| 911401555281 | SP560P LED40/840 L120W6 SD PSD | Yes | 911401556081 | SP560P LED40/840 L120W9 CD PSD | Yes |

Initial performance (IEC compliant)

SlimBalance G2

| Order Code | Full Product Name | Initial luminous flux | Initial input power |
|--------------|--------------------------------|-----------------------|---------------------|
| 911401550781 | SP560P LED6/840 L60W3 SD PSU | 645 lm | 6.5 W |
| 911401551281 | SP560P LED6/840 L60W3 CD PSU | 645 lm | 6.5 W |
| 911401552781 | SP560P LED12/840 L120W3 SD PSU | 1237 lm | 12 W |
| 911401553281 | SP560P LED12/840 L120W3 CD PSU | 1237 lm | 12 W |
| 911401550881 | SP560P LED12/840 L60W6 SD PSU | 1300 lm | 12 W |
| 911401550981 | SP560P LED20/840 L60W6 SD PSU | 2000 lm | 18 W |
| 911401551381 | SP560P LED12/840 L60W6 CD PSU | 1300 lm | 12 W |
| 911401551481 | SP560P LED20/840 L60W6 CD PSU | 2000 lm | 18 W |
| 911401552881 | SP560P LED25/840 L120W6 SD PSU | 2450 lm | 20 W |
| 911401552981 | SP560P LED40/840 L120W6 SD PSU | 4213 lm | 35 W |
| 911401553381 | SP560P LED25/840 L120W6 CD PSU | 2450 lm | 20 W |
| 911401553481 | SP560P LED40/840 L120W6 CD PSU | 4213 lm | 35 W |
| 911401555181 | SP560P LED20/840 L60W6 SD PSD | 2000 lm | 18 W |
| 911401555281 | SP560P LED40/840 L120W6 SD PSD | 4213 lm | 35 W |
| 911401555781 | SP560P LED20/840 L60W6 CD PSD | 2000 lm | 18 W |

| Order Code | Full Product Name | Initial luminous flux | Initial input power |
|---------------|--------------------------------|-----------------------|---------------------|
| 911401555881 | SP560P LED40/840 L120W6 CD PSD | 4213 lm | 35 W |
| 9114015551081 | SP560P LED12/840 L60W9 SD PSU | 1354 lm | 12 W |
| 9114015551181 | SP560P LED20/840 L60W9 SD PSU | 2083 lm | 18 W |
| 9114015551581 | SP560P LED12/840 L60W9 CD PSU | 1354 lm | 12 W |
| 9114015551681 | SP560P LED20/840 L60W9 CD PSU | 2083 lm | 18 W |
| 9114015553081 | SP560P LED25/840 L120W9 SD PSU | 2544 lm | 20 W |
| 9114015553181 | SP560P LED40/840 L120W9 SD PSU | 4374 lm | 35 W |
| 9114015553581 | SP560P LED25/840 L120W9 CD PSU | 2544 lm | 20 W |
| 9114015553681 | SP560P LED40/840 L120W9 CD PSU | 4374 lm | 35 W |
| 911401555381 | SP560P LED20/840 L60W9 SD PSD | 2083 lm | 18 W |
| 911401555481 | SP560P LED40/840 L120W9 SD PSD | 4374 lm | 35 W |
| 911401555981 | SP560P LED20/840 L60W9 CD PSD | 2083 lm | 18 W |
| 911401556081 | SP560P LED40/840 L120W9 CD PSD | 4374 lm | 35 W |

