



GreenPerform Highbay G5

BY698P G5 LED105/NW PSD NB GM

Lens

The GreenPerform Highbay G5 continues the GreenPerform family's enviable reputation for reliable performance. Not only does it deliver leading system efficacy and extended long-term quality, it also promises Unified Glare Rating (UGR) control with compact dimensions. GreenPerform Highbay G5 is also fully compatible with IoT software such as Interact, which is a scalable, future-proof control system. The family also has a series that supports cold room applications with 100% humidity and no condensation. All benefits that make this robust, optimized, and versatile family suitable for almost all industrial applications.

Product data

| General information | | Controls and dimming | |
|--|-------------------|-----------------------------|--|
| Light source color | 840 neutral white | Dimmable | Yes |
| Optical cover/lens type | Lens | Mechanical and housing | |
| Control interface | DALI | Housing Material | Aluminum die cast |
| Protection class IEC | Safety class I | Optical cover/lens material | Polycarbonate |
| CE mark | CE mark | Optical cover/lens finish | Clear |
| Number of products on MCB of 16 A type B 8 | | Overall height | 99 mm |
| Light source engine type | LED | Overall diameter | 330 mm |
| Operating and electrical | | Color | Dark gray |
| Input Voltage | 220 to 240 V | Approval and application | |
| Input Frequency | 50 or 60 Hz | Ingress protection code | IP65 [Dust penetration-protected, jet-proof] |
| Power Factor (Min) | 0.95 | | |

GreenPerform Highbay G5

| | |
|--|------------------------------|
| Mech. impact protection code | IK08 [5 J vandal-protected] |
| Initial performance (IEC compliant) | |
| Initial luminous flux (system flux) | 10500 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 150 lm/W |
| Init. Corr. Color Temperature | 4000 K |
| Init. Color Rendering Index | 80 |
| Initial chromaticity | (0.385, 0.380) SDCM<5 |
| Initial input power | 72 W |
| Power consumption tolerance | +/-10% |

Application conditions


| | |
|---------------------------|---------------|
| Ambient temperature range | -30 to +50 °C |
|---------------------------|---------------|

Product data

| | |
|---------------------------------|-------------------------------|
| Order product name | BY698P G5 LED105/NW PSD NB GM |
| Order code | 911401518691 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 1 |
| Material Nr. (12NC) | 911401518691 |
| Net Weight (Piece) | 3.540 kg |



Dimensional drawing



BY698P G5 LED105/NW PSD NB GM

