



GreenPerform Highbay G5

BY698X G5 LED200/CW Connected WB GM

Lens

The GreenPerform Highbay G5 continues the GreenPerform family's enviable reputation for reliable performance. Not only does it deliver leading system efficacy and extended long-term quality, it also promises Unified Glare Rating (UGR) control with compact dimensions. GreenPerform Highbay G5 is also fully compatible with IoT software such as Interact, which is a scalable, future-proof control system. The family also has a series that supports cold room applications with 100% humidity and no condensation. All benefits than make this robust, optimized, and versatile family suitable for almost all industrial applications.

Product data

General information		
Light source color	865 cool daylight	
Optical cover/lens type	Lens	
Control interface	InterAct Pro	
Protection class IEC	Safety class I	
CE mark	CE mark	
Number of products on MCB of 16	A type B 12	
Light source engine type	LED	
Operating and electrical		
Input Voltage	220 to 240 V	
Input Frequency	50 or 60 Hz	
Power Factor (Min)	0.95	

Controls and dimming		
Dimmable	Yes	
Mechanical and housing		
Housing Material	Aluminum die cast	
Optical cover/lens material	Polycarbonate	
Optical cover/lens finish	Clear	
Overall length	530 mm	
Overall width	393 mm	
Overall height	99 mm	
Color	Dark gray	

Datasheet, 2022, October 27 data subject to change

GreenPerform Highbay G5


Approval and application		
Ingress protection code	IP65 [Dust penetration-protected, jet-	
	proof]	
Mech. impact protection code	IK05 [0.7 J]	
Initial performance (IEC compliar	nt)	
Initial luminous flux (system flux)	20000 lm	
Luminous flux tolerance	+/-10%	
Initial LED luminaire efficacy	150 lm/W	
Init. Corr. Color Temperature	6500 K	
Init. Color Rendering Index	80	
Initial chromaticity	(0.316, 0.332) SDCM<5	
Initial input power	133 W	
Power consumption tolerance	+/-10%	

Application conditions	
Ambient temperature range	-30 to +50 ℃
Product data	
Order product name	BY698X G5 LED200/CW Connected WB GN
Order code	911401526591
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401526591
Net Weight (Piece)	5.290 kg





Dimensional drawing





BY698X G5 LED200/CW Connected WB GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any $quotation\ or\ contract,\ unless\ otherwise\ agreed\ by\ Signify.\ Philips\ and\ the\ Philips\ Shield\ Emblem\ are\ registered$ trademarks of Koninklijke Philips N.V.