



# GreenPerform Highbay G5

## BY698X G5 LED200/NW Connected WB GM

#### Lens

The GreenPerform Highbay G5 continues the GreenPerform family's enviable reputation for reliable performance. Not only does it deliver leading system efficacy and extended long-term quality, it also promises Unified Glare Rating (UGR) control with compact dimensions. GreenPerform Highbay G5 is also fully compatible with IoT software such as Interact, which is a scalable, future-proof control system. The family also has a series that supports cold room applications with 100% humidity and no condensation. All benefits than make this robust, optimized, and versatile family suitable for almost all industrial applications.

#### **Product data**

General information	
Light source color	840 neutral white
Optical cover/lens type	Lens
Control interface	InterAct Pro
Protection class IEC	Safety class I
CE mark	CE mark
Number of products on MCB of 16 A type	<b>B</b> 12
Light source engine type	LED
Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.95

Yes	
Aluminum die cast	
Polycarbonate	
Clear	
530 mm	
393 mm	
99 mm	
Dark gray	
	Aluminum die cast Polycarbonate Clear 530 mm 393 mm 99 mm

Datasheet, 2022, October 27 data subject to change

# **GreenPerform Highbay G5**


Approval and application	
Ingress protection code	IP65 [ Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK05 [ 0.7 J]
Initial performance (IEC complian	t)
Initial luminous flux (system flux)	20000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	150 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	80
Initial chromaticity	(0.385, 0.380) SDCM<5
Initial input power	133 W
Power consumption tolerance	+/-10%

Application conditions	
Ambient temperature range	-30 to +50 °C
Product data	
Order product name	BY698X G5 LED200/NW Connected WB GM
Order code	911401526391
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401526391
Net Weight (Piece)	5.290 kg





### Dimensional drawing





BY698X G5 LED200/NW Connected WB GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any  $quotation\ or\ contract,\ unless\ otherwise\ agreed\ by\ Signify.\ Philips\ and\ the\ Philips\ Shield\ Emblem\ are\ registered$ trademarks of Koninklijke Philips N.V.