



# GreenPerform Highbay G5

## BY698X G5 LED300/CW L1 W WB GM

Lens

The GreenPerform Highbay G5 continues the GreenPerform family's enviable reputation for reliable performance. Not only does it deliver leading system efficacy and extended long-term quality, it also promises Unified Glare Rating (UGR) control with compact dimensions. GreenPerform Highbay G5 is also fully compatible with IoT software such as Interact, which is a scalable, future-proof control system. The family also has a series that supports cold room applications with 100% humidity and no condensation. All benefits than make this robust, optimized, and versatile family suitable for almost all industrial applications.

#### **Product data**

865 cool daylight
Lens
BLE
Safety class I
For mounting on normally flammable
surfaces
CE mark
<b>уре В</b> б
LED
220 to 240 V
50 or 60 Hz

Inrush current	54 A
Power Factor (Min)	0.95
Controls and dimming	
Dimmable	Wireless Dim
Mechanical and housing	
Housing Material	Aluminum Alloy
Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Clear
Overall length	530 mm
Overall width	393 mm
Overall height	110 mm


### **GreenPerform Highbay G5**

Color	Gray
Approval and application	
Ingress protection code	IP65 [ Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK08 [ 6 J]
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	30000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	160 lm/W
Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.316, 0.332) SDCM<5
Initial input power	192 W
Power consumption tolerance	+/-10%

Application conditions	
Ambient temperature range	-30 to +50 °C
Product data	
Full product code	871951495512700
Order product name	BY698X G5 LED300/CW L1 W WB GM
EAN/UPC - Product	8719514955127
Order code	911401547402
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401547402
Net Weight (Piece)	4.490 kg



#### **Dimensional drawing**



BY698X G5 LED300/CW L1 W WB GM



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, January 10 - data subject to change