



# UniStrip G4

BCP386 12LED 27K 24V 60 L30

UniStrip G4 - 200 lm - 3 W - 2700 K

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

## Warnings and Safety

- For outdoor use only

## Product data

General information		Power Factor (Min)	0.9
Light source color	Warm white	<b>Controls and dimming</b>	
Driver included	No	Dimmable	No
Optical cover/lens type	Clear glass	<b>Mechanical and housing</b>	
Control interface	-	Housing Material	Aluminum extruded
Connection	2 Push-in connector 2-pole	Optical cover/lens material	Polymethyl methacrylate
Cable	2 cables 0.15m with connectors 2-pole	Overall length	300 mm
Protection class IEC	Safety class III	Overall width	25.4 mm
CE mark	CE mark	Overall height	71.6 mm
<b>Operating and electrical</b>		Color	Dark gray
Input Voltage	24 DC V		
Input Frequency	- Hz		

# UniStrip G4

## Approval and application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]

## Initial performance (IEC compliant)

Initial luminous flux (system flux)	200 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	67 lm/W
Init. Corr. Color Temperature	2700 K
Init. Color Rendering Index	80
Initial input power	3 W
Power consumption tolerance	+/-10%

## Application conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

## Product data

Full product code	871951451363199
Order product name	BCP386 12LED 27K 24V 60 L30
EAN/UPC - Product	8719514513631
Order code	911401779982
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	911401779982
Copy Net Weight (Piece)	0.360 kg



## Dimensional drawing



BCP386 12LED 27K 24V 60 L30

