



UniStrip G4

BCP386 12LED RGBWW 24V 45 L30 DMX

UniStrip G4 - 145 lm - 3 W - - K

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

| General information | | Power Factor (Min) | 0.9 |
|--------------------------|---------------------------------------|-----------------------------|-------------------------|
| Light source color | Red, green, blue and white | Controls and dimming | |
| Driver included | No | Dimmable | Yes |
| Optical cover/lens type | Clear glass | Mechanical and housing | |
| Control interface | Dynamic DMX | Housing Material | Aluminum extruded |
| Connection | 2 Push-in connector 5-pole | Optical cover/lens material | Polymethyl methacrylate |
| Cable | 2 cables 0.15m with connectors 5-pole | Overall length | 300 mm |
| Protection class IEC | Safety class III | Overall width | 25.4 mm |
| CE mark | CE mark | Overall height | 71.6 mm |
| | | Color | Dark gray |
| Operating and electrical | | | |
| Input Voltage | 24 DC V | | |
| Input Frequency | - Hz | | |

UniStrip G4

Approval and application

| | |
|------------------------------|---|
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |

Initial performance (IEC compliant)

| | |
|-------------------------------------|---------|
| Initial luminous flux (system flux) | 145 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 48 lm/W |
| Init. Corr. Color Temperature | - K |
| Init. Color Rendering Index | - |
| Initial input power | 3 W |
| Power consumption tolerance | +/-10% |

Application conditions


| | |
|---------------------------|---------------|
| Ambient temperature range | -40 to +50 °C |
|---------------------------|---------------|

Product data

| | |
|---------------------------------|-----------------------------------|
| Full product code | 871951451374799 |
| Order product name | BCP386 12LED RGBWW 24V 45 L30 DMX |
| EAN/UPC - Product | 8719514513747 |
| Order code | 911401780092 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 50 |
| Material Nr. (12NC) | 911401780092 |
| Net Weight (Piece) | 0.360 kg |



Dimensional drawing



BCP386 12LED RGBWW 24V 45 L30 DMX

