



# UniStrip G4

## BCP386 60LED 27K 24V 60 L100

UniStrip G4 - 985 lm - 15 W - 2700 K

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

### Warnings and Safety

- For outdoor use only

### Product data

General information		Power Factor (Min)	
Light source color	Warm white	0.9	
Driver included	No	Controls and dimming	
Optical cover/lens type	Clear glass	Dimmable	No
Control interface	-	Mechanical and housing	
Connection	2 Push-in connector 2-pole	Housing Material	Aluminum extruded
Cable	2 cables 0.15m with connectors 2-pole	Optical cover/lens material	Polymethyl methacrylate
Protection class IEC	Safety class III	Overall length	1000 mm
CE mark	CE mark	Overall width	25.4 mm
Operating and electrical		Overall height	71.6 mm
Input Voltage	24 DC V	Color	Dark gray
Input Frequency	- Hz		

# UniStrip G4

## Approval and application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]

## Initial performance (IEC compliant)

Initial luminous flux (system flux)	985 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	66 lm/W
Init. Corr. Color Temperature	2700 K
Init. Color Rendering Index	80
Initial input power	15 W
Power consumption tolerance	+/-10%

## Application conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

## Product data

Full product code	871951451413399
Order product name	BCP386 60LED 27K 24V 60 L100
EAN/UPC - Product	8719514514133
Order code	911401780482
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	911401780482
Copy Net Weight (Piece)	0.908 kg



## Dimensional drawing



BCP386 60LED 27K 24V 60 L100

