



UniStrip G4

BCP386 60LED RGB 24V A3 L100 DMX

UniStrip G4 - 345 lm - 15 W - - K

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

General information		Power Factor (Min)		0.9
Light source color	Red, green and blue	Controls and dimming		
Driver included	No	Dimmable	Yes	
Optical cover/lens type	Clear glass	Mechanical and housing		
Control interface	Dynamic DMX	Housing Material	Aluminum extruded	
Connection	2 Push-in connector 5-pole	Optical cover/lens material	Polymethyl methacrylate	
Cable	2 cables 0.15m with connectors 5-pole	Overall length	1000 mm	
Protection class IEC	Safety class III	Overall width	25.4 mm	
CE mark	CE mark	Overall height	71.6 mm	
		Color	Dark gray	
Operating and electrical				
Input Voltage	24 DC V			
Input Frequency	- Hz			

UniStrip G4

Approval and application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]

Initial performance (IEC compliant)

Initial luminous flux (system flux)	345 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	23 lm/W
Init. Corr. Color Temperature	- K
Init. Color Rendering Index	-
Initial input power	15 W
Power consumption tolerance	+/-10%

Application conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Product data

Full product code	871951451430099
Order product name	BCP386 60LED RGB 24V A3 L100 DMX
EAN/UPC - Product	8719514514300
Order code	911401780652
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	911401780652
Net Weight (Piece)	0.908 kg



Dimensional drawing



BCP386 60LED RGB 24V A3 L100 DMX

