



UniBar

BCS341 18LED 40K 24V OC L30

UniBar - 215 lm - 4 W - 4000 K

UniBar is a surface mounted, exterior-rated and slim sized linear LED direct view luminaire that is designed for façade and outdoor architectural lighting applications. The robust mechanical and unique optical design make it ideal for buildings facades, media facades, bridges, overpasses and any application that requires a slim linear direct view lighting solution. Direct view spread lens, through wiring for end-to-end connection and DMX control option available with up to 10 pixels (10IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations. Available in white, monochromatic colors, RGB, RGBW and tunable white.

Product data

| General information | |
|-------------------------|--|
| Light source color | Neutral white |
| Driver included | No |
| Optical cover/lens type | Opal |
| Control interface | - |
| Connection | 2 Push-in connector 2-pole |
| Cable | 2 cables (0.2m input + 0.1m output) with connectors 2-pole |
| Protection class IEC | Safety class III |
| CE mark | CE mark |

| Operating and electrical | |
|--------------------------|---------|
| Input Voltage | 24 DC V |
| Input Frequency | - Hz |
| Power Factor (Min) | 0.9 |

| Controls and dimming | |
|----------------------|----|
| Dimmable | No |

| Mechanical and housing | |
|-----------------------------|-------------------|
| Housing Material | Aluminum extruded |
| Optical cover/lens material | Polycarbonate |
| Overall length | 300 mm |
| Overall width | 35 mm |
| Overall height | 65 mm |
| Color | Silver |

| Approval and application | |
|------------------------------|---|
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK08 [5 J vandal-protected] |

Initial performance (IEC compliant)

| | |
|-------------------------------------|---------|
| Initial luminous flux (system flux) | 215 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 53 lm/W |
| Init. Corr. Color Temperature | 4000 K |
| Init. Color Rendering Index | 80 |
| Initial input power | 4 W |
| Power consumption tolerance | +/-10% |

Application conditions


| | |
|---------------------------|---------------|
| Ambient temperature range | -40 to +50 °C |
|---------------------------|---------------|

Product data

| | |
|---------------------------------|-----------------------------|
| Full product code | 911401779332 |
| Order product name | BCS341 18LED 40K 24V OC L30 |
| Order code | 911401779332 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 48 |
| Material Nr. (12NC) | 911401779332 |
| Copy Net Weight (Piece) | 0.291 kg |



Dimensional drawing



BCS341 18LED 40K 24V OC L30

