

UNILinear Flex

BGC401 550LM 7W 3500K L5 1515 S G

UNILinear Flex - 2750 lm - 35 W - 3500 K

UNILinear Flex is really and excellently waterproof and anti-dust LED strips with professional design to guarantee lighting performance. Thanks to filling with anti-UV polyurethane and processing by irrigation methods sealing glue, it not only ensure high quality of lighting color consistency but also protect products outdoor against from harsh environments outdoors. It's can be used for decoration lighting and guidance lighting outdoors, the higher CRI (80) delivers good performance of lighting in color rendering.

Product data

General information	
Light source color	935 warm white
Driver included	No
Optical cover/lens type	Opal
Control interface	-
Connection	Flying leads/wires
Cable	Cable 0.6 m without plug
Protection class IEC	Safety class III
CE mark	CE mark
Constant light output	No

Operating and electrical	
Input Voltage	24 DC V
Input Frequency	- Hz
Power Factor (Min)	-

Controls and dimming	
Dimmable	No

Mechanical and housing	
Housing Material	Silicon rubber
Optical cover/lens material	Silicon rubber
Fixation material	Stainless steel
Overall length	15 mm
Overall width	5000 mm
Overall height	15 mm
Color	White

Approval and application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK04 [0.5 J standard plus]

Initial performance (IEC compliant)	
Initial luminous flux (system flux)	2750 lm

UNILinear Flex

Luminous flux tolerance	-10%,+15%
Initial LED luminaire efficacy	73 lm/W
Init. Corr. Color Temperature	3500 K
Init. Color Rendering Index	>90
Initial chromaticity	4 SDCM
Initial input power	35 W
Power consumption tolerance	+/-10%

Application conditions

Ambient temperature range	-40 to +45 °C
---------------------------	---------------


Product data

Full product code	692382863730900
-------------------	-----------------

Order product name	BGC401 550LM 7W 3500K L5 1515 S G
EAN/UPC - Product	6923828637309
Order code	911401767772
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	911401767772
Copy Net Weight (Piece)	1.470 kg



Dimensional drawing



BGC401 550LM 7W 3500K L5 1515 S G

