



# GreenVision Xceed Gen2

## BRP381 LED138/WW 105W 220-240V DM PSR

GreenVision Xceed Gen2 - 13800 lm - 105 W - 3000 K

Sustainability, citizen well being and connectivity are key players in the game of differentiation among cities all over the world. And a way of achieving this goals is lighting; Lighting up streets and roads enhance the comfort, security and overall safety of our rapidly growing urban environments. Our GreenVision Xceed Gen2 makes an affordable LED road lighting solution that ensures sufficient light on your roads & streets; The GreenVision Xceed Gen2 family from Signify provides your city with a flexible lighting system which can be deployed anywhere in urban spaces, highways and rural areas – our luminaires provide the optimal light for all application areas. And, GreenVision Xceed Gen2 is ready to be connected and work with smart city ecosystem; Our new GreenVision Xceed Gen2 range is enhanced to give city lighting departments even more control – to choose the right light

### Product data

General information		Operating and electrical	
Light source color	730 warm white	CE mark	CE mark
Light source replaceable	No	Warranty period	3 years
Driver/power unit/transformer	Power supply unit regulating	Constant light output	No
Driver included	Yes	Input Voltage	220 to 240 V
Optical cover/lens type	Polycarbonate micro lens optic	Input Frequency	50 or 60 Hz
Control interface	Analog	Power Factor (Min)	0.9
Connection	-		
Cable	-		
Protection class IEC	Safety class I		
Flammability mark	For mounting on normally flammable surfaces		

## GreenVision Xceed Gen2

### Controls and dimming

Dimmable	Yes
----------	-----

### Mechanical and housing

Housing Material	Aluminum die cast
Optic material	Polycarbonate
Optical cover/lens material	Glass
Fixation material	Aluminum
Overall length	446 mm
Overall width	310 mm
Overall height	138 mm
Effective projected area	0.14 m <sup>2</sup>
Color	Gray

### Approval and application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [ 5 J vandal-protected]

### Initial performance (IEC compliant)

Initial luminous flux (system flux)	13800 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	133 lm/W
Init. Corr. Color Temperature	3000 K

Init. Color Rendering Index	>70
Initial chromaticity	(0.43, 0.40) SDCM < 5
Initial input power	105 W
Power consumption tolerance	+/-10%

### Over time performance (IEC compliant)

Median useful life L70B50	100000 h
---------------------------	----------

### Application conditions


Ambient temperature range	-40 to +50 °C
Maximum dim level	10%

### Product data

Full product code	911401877698
Order product name	BRP381 LED138/WW 105W 220-240V DM PSR
Order code	911401877698
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401877698
Copy Net Weight (Piece)	5.299 kg



## Dimensional drawing



BRP381 LED138/WW 105W 220-240V DM PSR

