

UniFlood G

BVP344 216LED RGBNW 220V 15x17 DMX D3

UniFlood G - 29547 lm - 520 W - - K

UniFlood G is a giant, high power, rectangular shaped and exterior-rated architectural LED floodlight that is designed for façade, landscape and outdoor flood lighting applications.;The robust mechanical design and high-efficient optical design make it ideal for illuminating high story exterior facades, bridges, landmarks and monuments.;Available in white, monochromatic colors, RGB, RGBW and tunable white.;Eight different spread lenses ranging from narrow spot, to wide flood and DMX512/RDM control option available to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Product data

General information	
Light source color	Red, green, blue and white
Driver included	Yes
Optical cover/lens type	Tempered glass
Control interface	Dynamic DMX/RDM
Connection	Flying leads/wires and 2 Push-in connector 4-pole
Cable	Cable 0.5 m without plug 3-pole and 2 Cables 0.5 m
	with connector 4-pole
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Inrush current	180 A

Power Factor (Min)	0.9	
Controls and dimming		
Dimmable	Yes	
Mechanical and housing		
Housing Material	Aluminum die cast	
Optical cover/lens material	Polymethyl methacrylate	
Effective projected area	1.1 m²	
Color	Dark gray	
Approval and application		
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK09 [10 J]	
Initial performance (IEC compliant)		
Initial luminous flux (system flux) 29547 lm		

Datasheet, 2022, October 27 data subject to change

UniFlood G

Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	57 lm/W
Init. Corr. Color Temperature	- K
Init. Color Rendering Index	-
Initial chromaticity	-
Initial input power	520 W
Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-40 to +50 °C

871951453769900

Order product name	BVP344 216LED RGBNW 220V 15x17 DMX D3
EAN/UPC - Product	8719514537699
Order code	911401730023
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	¢ 1
Material Nr. (12NC)	911401730023
Net Weight (Piece)	55.999 kg








Dimensional drawing

Product data Full product code



BVP344 216LED RGBNW 220V 15x17 DMX D3



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any $quotation\ or\ contract,\ unless\ otherwise\ agreed\ by\ Signify.\ Philips\ and\ the\ Philips\ Shield\ Emblem\ are\ registered$ trademarks of Koninklijke Philips N.V.