

# **UniFlood G**

#### **BVP344 96LED RGBNW 220V 3 DMX D2**

UniFlood G - 10963 lm - 240 W - - K

UniFlood G is a giant, high power, rectangular shaped and exterior-rated architectural LED floodlight that is designed for façade, landscape and outdoor flood lighting applications.;The robust mechanical design and high-efficient optical design make it ideal for illuminating high story exterior facades, bridges, landmarks and monuments.;Available in white, monochromatic colors, RGB, RGBW and tunable white.;Eight different spread lenses ranging from narrow spot, to wide flood and DMX512/RDM control option available to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

#### **Product data**

General information	
Light source color	Red, green, blue and white
Driver included	Yes
Optical cover/lens type	Tempered glass
Control interface	Dynamic DMX/RDM
Connection	Flying leads/wires and 2 Push-in connector 4-pole
Cable	Cable 0.5 m without plug 3-pole and 2 Cables 0.5 m
	with connector 4-pole
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Inrush current	140 A

Power Factor (Min)	0.9	
Controls and dimming		
Dimmable	Yes	
Mechanical and housing		
Housing Material	Aluminum die cast	
Optical cover/lens material	Polymethyl methacrylate	
Effective projected area	1.1 m²	
Color	Dark gray	
Approval and application		
Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK09 [ 10 J]	
Initial performance (IEC compliant)		
Initial luminous flux (system flux) 10963 lm		

Datasheet, 2022, July 26 data subject to change

### **UniFlood G**

Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	46 lm/W
Init. Corr. Color Temperature	- K
Init. Color Rendering Index	-
Initial chromaticity	-
Initial input power	240 W
Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-40 to +50 °C

871951453753800

Order product name	BVP344 96LED RGBNW 220V 3 DMX D2
EAN/UPC - Product	8719514537538
Order code	911401729863
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	: 1
Material Nr. (12NC)	911401729863
Net Weight (Piece)	55.999 kg








## Dimensional drawing

Product data Full product code



**BVP344 96LED RGBNW 220V 3 DMX D2** 



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any  $quotation\ or\ contract,\ unless\ otherwise\ agreed\ by\ Signify.\ Philips\ and\ the\ Philips\ Shield\ Emblem\ are\ registered$ trademarks of Koninklijke Philips N.V.