PHILIPS Lighting



Tango G4 LED Flood

BVP432 LED161/CW 220~240V 120W SWB GM

Tango G4 LED Flood - 16100 lm - 120 W - 5700 K

Philips Tango G4 LED Floodlight is the 4th generation of the Tango LED family. A new range lighting that delivers higher efficacy and has an optimized windage area, and less weight thanks to its technical design. This product introduction is the ideal solution for a wide range of area lighting and recreational sports lighting applications. It incorporates the latest LED light source, one-piece optical system, heat sink and driver into a compact and robust housing that meets globally-recognized safety standards. Its specially-designed heat sink incorporates aesthetics and functionality to ensure excellent reliability. Powered by LED technology, Tango G4 LED floodlights deliver superior performance and a longer lifetime, bringing area lighting to a whole new level.

Warnings and Safety

please pay attention to the mounting instructions

Product data

General information		Input Frequency	50 or 60 Hz
Light source color	757 cool white	Power Factor (Min)	0.9
Driver included	Yes		
Optical cover/lens type	Polycarbonate bowl/cover	Controls and dimming	
Control interface	-	Dimmable	No
Connection	Flying leads/wires		
Cable	Cable 1.5 m without plug	Mechanical and housing	
Protection class IEC	Safety class I	Housing Material	Aluminum die cast
CE mark	CE mark	Optical cover/lens material	Polycarbonate
		Overall length	347 mm
Operating and electrical		Overall width	414 mm
Input Voltage	220 to 240 V	Overall height	77 mm


Tango G4 LED Flood

approval and application approval and application IP		
ngress protection code IP		
	IP66 [Dust penetration-protected, jet-proof]	
lech. impact protection code	IK08 [5 J vandal-protected]	
Initial performance (IEC compliant)		
nitial luminous flux (system flux) 16	16100 lm	
uminous flux tolerance +/	+/-10%	
nitial LED luminaire efficacy 13	134.1666666666666666 lm/W	
nit. Corr. Color Temperature 57	5700 K	
nit. Color Rendering Index >7	>70	
nitial input power 12	0 W	
ower consumption tolerance +/	+/-10%	

Application conditions		
Ambient temperature range	-40 to +50 °C	
Product data		
Full product code	871951454049100	
Order product name	BVP432 LED161/CW 220~240V 120W SWB GM	
EAN/UPC - Product	8719514540491	
Order code	911401687606	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	1	
Material Nr. (12NC)	911401687606	
Copy Net Weight (Piece)	6.190 kg	



Dimensional drawing



BVP432 LED161/CW 220~240V 120W SWB GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2022, July 15 - data subject to change