



# Tango G4 LED Flood

## BVP433 LED286/NW 220~240V 230W SAWB GM

Tango G4 LED Flood - 28600 lm - 230 W - 4000 K

Philips Tango G4 LED Floodlight is the 4th generation of the Tango LED family. A new range lighting that delivers higher efficacy and has an optimized windage area, and less weight thanks to its technical design. This product introduction is the ideal solution for a wide range of area lighting and recreational sports lighting applications. It incorporates the latest LED light source, one-piece optical system, heat sink and driver into a compact and robust housing that meets globally-recognized safety standards. Its specially-designed heat sink incorporates aesthetics and functionality to ensure excellent reliability. Powered by LED technology, Tango G4 LED floodlights deliver superior performance and a longer lifetime, bringing area lighting to a whole new level.

### Warnings and Safety

- please pay attention to the mounting instructions

### Product data

General information	
Light source color	740 neutral white
Driver included	Yes
Optical cover/lens type	Polycarbonate bowl/cover
Control interface	-
Connection	Flying leads/wires
Cable	Cable 1.5 m without plug
Protection class IEC	Safety class I
CE mark	CE mark
Operating and electrical	
Input Voltage	220 to 240 V

Input Frequency	50 or 60 Hz
Power Factor (Min)	0.9
Controls and dimming	
Dimmable	No
Mechanical and housing	
Housing Material	Aluminum die cast
Optical cover/lens material	Polycarbonate
Overall length	523 mm
Overall width	559 mm
Overall height	71 mm

# Tango G4 LED Flood


Color	Gray
<b>Approval and application</b>	
Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [ 5 J vandal-protected]
<b>Initial performance (IEC compliant)</b>	
Initial luminous flux (system flux)	28600 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	124.34782608695652 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>70
Initial input power	230 W
Power consumption tolerance	+/-10%

## Application conditions


Ambient temperature range -40 to +50 °C

## Product data

Full product code	871951454035400
Order product name	BVP433 LED286/NW 220~240V 230W SAWB GM
EAN/UPC - Product	8719514540354
Order code	911401695806
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401695806
Copy Net Weight (Piece)	12.160 kg



## Dimensional drawing



BVP433 LED286/NW 220~240V 230W SAWB GM

