# **PHILIPS** Lighting



# Tango G4 LED Flood

## BVP433 LED382/NW 220~240V 305W SAWB GM

Tango G4 LED Flood - 38200 lm - 305 W - 4000 K

Philips Tango G4 LED Floodlight is the 4th generation of the Tango LED family. A new range lighting that delivers higher efficacy and has an optimized windage area, and less weight thanks to its technical design. This product introduction is the ideal solution for a wide range of area lighting and recreational sports lighting applications. It incorporates the latest LED light source, one-piece optical system, heat sink and driver into a compact and robust housing that meets globally-recognized safety standards. Its specially-designed heat sink incorporates aesthetics and functionality to ensure excellent reliability. Powered by LED technology, Tango G4 LED floodlights deliver superior performance and a longer lifetime, bringing area lighting to a whole new level.

#### Warnings and Safety

 $\cdot$  please pay attention to the mounting instructions

#### Product data

	Input Frequency	50 or 60 Hz
740 neutral white	Power Factor (Min)	0.9
Yes		
Polycarbonate bowl/cover	Controls and dimming	
-	Dimmable	No
Flying leads/wires		
Cable 1.5 m without plug	Mechanical and housing	
Safety class I	Housing Material	Aluminum die cast
CE mark CE mark	Optical cover/lens material	Polycarbonate
	Overall length	523 mm
	Overall width	559 mm
220 to 240 V	Overall height	71 mm
	Yes Polycarbonate bowl/cover - Flying leads/wires Cable 1.5 m without plug Safety class I CE mark	740 neutral white Power Factor (Min)   Yes Controls and dimming   Polycarbonate bowl/cover Controls and dimming   - Dimmable   Flying leads/wires Dimmable   Cable 1.5 m without plug Mechanical and housing   Safety class I Housing Material   CE mark Optical cover/lens material   Overall length Overall width


### Tango G4 LED Flood

Color	Gray	
Approval and application		
Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK08 [ 5 J vandal-protected]	
Initial performance (IEC compliant)		
Initial luminous flux (system flux)	38200 lm	
Luminous flux tolerance	+/-10%	
Initial LED luminaire efficacy	125.24590163934427 lm/W	
Init. Corr. Color Temperature	4000 K	
Init. Color Rendering Index	>70	
Initial input power	305 W	
Power consumption tolerance	+/-10%	

Application conditions	
Ambient temperature range	-40 to +50 °C
Product data	
Full product code	871951454095800
Order product name	BVP433 LED382/NW 220~240V 305W SAWB GM
EAN/UPC - Product	8719514540958
Order code	911401601207
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401601207
Copy Net Weight (Piece)	12.160 kg



#### Dimensional drawing



BVP433 LED382/NW 220~240V 305W SAWB GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2022, July 15 - data subject to change