



Tango G4 LED Flood

BVP433 LED517/NW 220~240V 380W SWB GM

Tango G4 LED Flood - 51700 lm - 380 W - 4000 K

Philips Tango G4 LED Floodlight is the 4th generation of the Tango LED family. A new range lighting that delivers higher efficacy and has an optimized windage area, and less weight thanks to its technical design. This product introduction is the ideal solution for a wide range of area lighting and recreational sports lighting applications. It incorporates the latest LED light source, one-piece optical system, heat sink and driver into a compact and robust housing that meets globally-recognized safety standards. Its specially-designed heat sink incorporates aesthetics and functionality to ensure excellent reliability. Powered by LED technology, Tango G4 LED floodlights deliver superior performance and a longer lifetime, bringing area lighting to a whole new level.

Warnings and Safety

- please pay attention to the mounting instructions

Product data

| General information | |
|--------------------------|--------------------------|
| Light source color | 740 neutral white |
| Driver included | Yes |
| Optical cover/lens type | Polycarbonate bowl/cover |
| Control interface | - |
| Connection | Flying leads/wires |
| Cable | Cable 1.5 m without plug |
| Protection class IEC | Safety class I |
| CE mark | CE mark |
| Operating and electrical | |
| Input Voltage | 220 to 240 V |

| Input Frequency | 50 or 60 Hz |
|-----------------------------|-------------------|
| Power Factor (Min) | 0.9 |
| Controls and dimming | |
| Dimmable | No |
| Mechanical and housing | |
| Housing Material | Aluminum die cast |
| Optical cover/lens material | Polycarbonate |
| Overall length | 523 mm |
| Overall width | 559 mm |
| Overall height | 71 mm |

Tango G4 LED Flood


| | |
|--|---|
| Color | Gray |
| Approval and application | |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK08 [5 J vandal-protected] |
| Initial performance (IEC compliant) | |
| Initial luminous flux (system flux) | 51700 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 136.05263157894737 lm/W |
| Init. Corr. Color Temperature | 4000 K |
| Init. Color Rendering Index | >70 |
| Initial input power | 380 W |
| Power consumption tolerance | +/-10% |

Application conditions


Ambient temperature range -40 to +50 °C

Product data

| | |
|---------------------------------|---------------------------------------|
| Full product code | 871951454073600 |
| Order product name | BVP433 LED517/NW 220~240V 380W SWB GM |
| EAN/UPC - Product | 8719514540736 |
| Order code | 911401606607 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 1 |
| Material Nr. (12NC) | 911401606607 |
| Copy Net Weight (Piece) | 12.160 kg |



Dimensional drawing



BVP433 LED517/NW 220~240V 380W SWB GM

