



# UniString

## BWS301 6LED 30K 24V A TM LR N16P12

UniString - 87 lm - 1.5 W - 3000 K

UniString is a surface mounted, exterior-rated and compact sized architectural LED direct view string that is designed for architectural and media façade outdoor lighting applications.;The robust mechanical design, easy installation and unique optical lenses make UniString ideal for buildings/media facades, bridges, arenas, theaters, amusement parks and recreational centers.;Available in white, monochromatic colors, RGB, RGBW and tunable white.;Available in symmetrical and asymmetrical optical distributions with DMX control option to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

### Warnings and Safety

- For outdoor use only

### Product data

General information		CE mark	
Light source color	Warm white		CE mark
Light source replaceable	No	<b>Operating and electrical</b>	
Driver included	No	Input Voltage	24 DC V
Optical cover/lens type	Polycarbonate bowl/cover clear	Input Frequency	- Hz
Luminaire light beam spread	85° x 110°	Power Factor (Min)	0.9
Control interface	-	<b>Controls and dimming</b>	
Connection	Push-in connector 2-pole	Dimmable	No
Cable	2 meters long cable with 16 nodes, 125mm pitch and 2 connectors 2-pole	<b>Mechanical and housing</b>	
Protection class IEC	Safety class III	Housing Material	Polycarbonate
Glow-wire test	Temperature 750 °C, duration 30 s	Optical cover/lens material	Polycarbonate
Flammability mark	For mounting on normally flammable surfaces		

# UniString

Overall length	47 mm
Overall width	15.5 mm
Overall height	57 mm
Color	Black

## Approval and application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]

## Initial performance (IEC compliant)

Initial luminous flux (system flux)	87 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	58 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	80
Initial chromaticity	4 SDCM
Initial input power	1.5 W

Power consumption tolerance	+/-10%
-----------------------------	--------

## Application conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

## Product data

Full product code	911401753612
Order product name	BWS301 6LED 30K 24V A TM LR N16P12
Order code	911401753612
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401753612
Copy Net Weight (Piece)	0.750 kg



## Dimensional drawing



BWS301 6LED 30K 24V A TM LR N16P12

