

# **Greenspace Flex**

## RS378B MR16 D78 R-R FX D

Accessory - Greenspace Flex

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

#### **Product data**

General information	
Beam angle of light source	- °
Light source color	-
Number of gear units	1 unit
Driver/power unit/transformer	Electronic transformer
Driver included	No
Optic type	-
Optical cover/lens type	=
Luminaire light beam spread	-
Control interface	-
Connection	External connector
Cable	-
Protection class IEC	-
Glow-wire test	Temperature 600 °C, duration 30 s
Flammability mark	-
CE mark	-
ENEC mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	-
EU RoHS compliant	Yes

Light source engine type	LED
Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Power Factor (Min)	-
Controls and dimming	
Dimmable	No
Mechanical and housing	
Housing Material	Aluminum
Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover/lens material	-
Fixation material	Aluminum
Optical cover/lens finish	-
Overall length	0 mm
Overall width	0 mm
Overall height	104 mm
Overall diameter	85 mm

Datasheet, 2022, June 14 data subject to change


# **Greenspace Flex**

Color	Gray
Dimensions (Height x Width x Depth)	104 x 0 x 0 mm
Approval and application	
Ingress protection code	IP20 [ Finger-protected]
Mech. impact protection code	IK04 [ 0.5 J standard plus]
Initial performance (IEC compliant)	
Luminous flux tolerance	+/-10%
Init. Corr. Color Temperature	- K
Init. Color Rendering Index	-
Initial input power	- W
Power consumption tolerance	+/-10%
Over time performance (IEC compliant)	
Median useful life L80B50	50000 h

Application conditions	
Ambient temperature range	-20 to +45 °C
Maximum dim level	Not applicable
Suitable for random switching	No
Product data	
Full product code	911401720832
Order product name	RS378B MR16 D78 R-R FX D
Order code	911401720832
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	36
Material Nr. (12NC)	911401720832
Net Weight (Piece)	0.170 kg



## Dimensional drawing



Cut out: Ø102

RS378B MR16 D78 R-R FX D



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.