
PHILIPS Lighting



Greenspace Flex

RS378B MR16 D78 S-S AJ D

Accessory - Greenspace Flex

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

Product data

| General information | |
|--|-----------------------------------|
| Beam angle of light source | _ ° |
| Light source color | - |
| Number of gear units | 1 unit |
| Driver/power unit/transformer | Electronic transformer |
| Driver included | No |
| Optic type | - |
| Optical cover/lens type | - |
| Luminaire light beam spread | - |
| Control interface | - |
| Connection | External connector |
| Cable | - |
| Protection class IEC | - |
| Glow-wire test | Temperature 600 °C, duration 30 s |
| Flammability mark | - |
| CE mark | - |
| ENEC mark | - |
| Warranty period | 3 years |
| Constant light output | No |
| Number of products on MCB of 16 A type B | - |
| EU RoHS compliant | Yes |
| | |

| Light source engine type | LED |
|-----------------------------|-------------------------|
| | |
| Operating and electrical | |
| Input Voltage | 220 to 240 V |
| Input Frequency | 50 to 60 Hz |
| Power Factor (Min) | - |
| | |
| Controls and dimming | |
| Dimmable | No |
| | |
| Mechanical and housing | |
| Housing Material | Aluminum |
| Reflector material | - |
| Optic material | Polymethyl methacrylate |
| Optical cover/lens material | - |
| Fixation material | Aluminum |
| Optical cover/lens finish | - |
| Overall length | 85 mm |
| Overall width | 85 mm |
| Overall height | 104 mm |
| Overall diameter | 0 mm |
| | |


Greenspace Flex

| Color | Gray |
|---------------------------------------|-----------------------------|
| Dimensions (Height x Width x Depth) | 104 x 85 x 85 mm |
| | |
| Approval and application | |
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK04 [0.5 J standard plus] |
| | |
| Initial performance (IEC compliant) | |
| Luminous flux tolerance | +/-10% |
| Init. Corr. Color Temperature | - K |
| Init. Color Rendering Index | - |
| Initial input power | - W |
| Power consumption tolerance | +/-10% |
| | |
| Over time performance (IEC compliant) | |
| Median useful life L80B50 | 50000 h |

| Application conditions | |
|---------------------------------|--------------------------|
| Ambient temperature range | -20 to +45 °C |
| Maximum dim level | Not applicable |
| Suitable for random switching | No |
| | |
| Product data | |
| Full product code | 911401720842 |
| Order product name | RS378B MR16 D78 S-S AJ D |
| Order code | 911401720842 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 36 |
| Material Nr. (12NC) | 911401720842 |
| Net Weight (Piece) | 0.150 kg |
| | |



Dimensional drawing





Cut out: Ø78

RS378B MR16 D78 S-S AJ D



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2022, June 14 - data subject to change