



Greenspace Flex

RS378Z M55 D75 R-R AJ PH

Accessory - Greenspace Flex

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

Product data

General information	
Light source color	-
Optical cover/lens type	-
Control interface	-
Cable	-
Protection class IEC	-
CE mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	-
Light source engine type	-
Operating and electrical	
Input Voltage	- V
Input Frequency	- Hz
Power Factor (Min)	-
Mechanical and housing	
Housing Material	Aluminum
Optical cover/lens material	-
Fixation material	Aluminum

Optical cover/lens finish	-
Overall length	0 mm
Overall width	0 mm
Overall height	48 mm
Overall diameter	88 mm
Color	White
Dimensions (Height x Width x Depth)	48 x 0 x 0 mm
Approval and application	
Ingress protection code	-
Mech. impact protection code	IK04 [0.5 J standard plus]
Initial performance (IEC compliant)	
Init. Corr. Color Temperature	- K
Init. Color Rendering Index	-
Initial input power	- W
Application conditions	
Ambient temperature range	-20 to +45 °C
Maximum dim level	Not applicable

Greenspace Flex



Product data

Full product code	911401721872
Order product name	RS378Z M55 D75 R-R AJ PH
Order code	911401721872
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	48

Material Nr. (12NC)	911401721872
Net Weight (Piece)	0.120 kg

IK04

Dimensional drawing



Cut out: Ø75

RS378Z M55 D75 R-R AJ PH

